



8245 Flat Roof Coat-N-Seal Liquid Rubber Coating

- Stop and Seals Leaks on Worn Roofs
- Permanent 100% Waterproof Finish
- Commercial-Grade Durability
- One Coat Application

Gardner® Flat Roof Coat-N-Seal FRS-1® is formulated specifically to restore and waterproof worn roof surfaces. Ideal for commercial or residential flat or low slope roof surfaces. Great choice for built up roofs, concrete roofs, parapet walls, foam, RV's, rubber, mobile homes, EPDM and TPO roofs. Easy and fast to apply, plus delivers superior waterproofing protection that will provide a permanent seal for the life of the roof. The rubberized finish expands and contracts to resist cracking, and reduces thermal shock. UV inhibitors reflect and keep surfaces cooler which allow the roof to ultimately last longer. This fast set moisture-cure product, delivers superior waterproofing and sealing, and is well suited to be used in hot or cold climates.

PREPARATION: Repair leaks and damaged areas with Black Jack® Silicone Roof Patch. Power wash clean all surfaces, and remove dirt and grime with a degreaser/cleaner. If mold is present, clean with a proper bleach solution (1 part bleach to 2 parts water). Allow roof to dry 24 hours before coating. For applications over asphalt roof surfaces, apply Black Jack® Stain-Stop Primer as a base coat for proper stain blocking protection.

APPLICATION: Mix well before applying. A power drill mixing tool is ideal. Confirm all dew or moisture has completely dried from the roof before applying. Best applied on a clear, dry day with warming temps between 35 °F and 120 °F. Use a quality, heavy duty 3/4" nap paint roller.

COATING APPLICATION: This coating can be applied in 1 coat to surfaces in good condition. Spread at 71 sq/ft per gallon which will yield a dry film of 22 mils. Recoat rough or damaged areas as needed.

COVERAGE RATE: Container covers approximately 335 sq/ft at a 22 mil dry film thickness on smooth surfaces, apply heavier coat on rough surfaces.

COMPLIANCE: CRRC rated, FL Building Code and Miami-Dade County approved, ASTM D6694, ASTM D7281. NSF Certified and meets the requirements of CEC Title 24.

CLEAN-UP: Clean tools immediately with mineral spirits.

PRECAUTIONS: For exterior use only. Protect building inlets from product vapors or fumes. DO NOT allow product to freeze. Protective clothing, gloves and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. For longest life, store in controlled environment, 45 °F - 80 °F. DO NOT store in direct sunlight. DO NOT store at temperatures above 99 °F. Close container after use. DO NOT reuse empty containers. Ponding water creates excessive weight on roofs and may compromise structural integrity leading to a potential collapse hazard. Always follow the National Roofing Contractors Association guidelines to remove ponding water from roof surfaces. Slip Warning: Use extreme caution when walking or working on silicone coated surfaces. Surface is extremely slippery and can create a fall hazard resulting in injury or death. Use OSHA approved fall protection when on roof surfaces.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants this product to be free of material defects. Product must be used for the intended use stated on the label and applied to a sound roof with a reasonable life expectancy. If a product defect is found, Gardner-Gibson shall, within its sole discretion, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim. Proper preparation, application procedures and curing conditions are required for correct results. Due to installation factors beyond our control, Gardner-Gibson cannot guarantee product appearance, waterproofing or compatibility with existing roof. Warranty is void if other materials are installed on top of it. To transfer warranty, see details on website. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company to request a refund or replacement with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-8245	4.75 gal	12" x 12" x 14.75"	4.75 gal/18 L	52 lbs.	1 ea.	025056824554

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101