

DRIVEASEAL

0595 Driveaseal Blacktop Driveway Sealer

DESCRIPTION: Driveaseal Blacktop Sealer is an economical asphalt pavement coating designed to seal surfaces in good condition. This coating will restore a black finish to asphalt surfaces. Surfaces must be in good repair prior to applying this product. NOT intended for high traffic areas. DO NOT USE ON CONCRETE, FLAGSTONE, BRICK OR CLAY SURFACES.

PREPARATION: Driveways must be cleaned before sealcoating. Treat oil stain & spots with cleaner to prevent adhesion failures. Repair cracks and holes with suitable crack filler & patching products. Sweep surface clean and/or rinse thoroughly to remove dust and debris. Do not allow puddling of water.

FOR BEST RESULTS: Apply on warm days during the summer, in the morning hours of a clear day. Apply perpendicular to the street entrance, this hides application imperfections. If possible, use pails containing the same batch code stamp on the top of the lid. Remember to mix all buckets to a uniform consistency, and when using multiple buckets, blend the end of one bucket with the beginning of the next to prevent shade variances. Allow to cure 24-36 hours before vehicle traffic. Do not apply on newly laid pavements until at least one full summer's season of weathering has occurred.

APPLICATION: Turn all pails upside down the night before, or at least prior to sealcoating. Temperatures must be 60 °F and rising, but below 90 °F during application. Clean driveway and thoroughly rinse. Remove puddles and then apply sealer to a slightly damp surface (not wet). MIX WELL. A small amount of water separation in the pail is normal, and should be easily mixed in. Pour out 1/3 of the container and spread product across the blacktop surface with a squeegee. Squeegee must be used to spread product and for proper application rates. After application with squeegee, a follow up with a brush may be used if a textured surface is desired. Complete the entire driveway in one continuous application to prevent "color shading". If multiple pails are used, it is best to match batch codes and blend the end of one pail into the beginning of the other to maintain consistent coloring and texture. Do not over apply as this may lead to tracking. Do not apply if rain or cold temperatures are expected within 36 hours. This sealer is not recommended or warranted for use on surfaces containing slopes of greater than 20°.

COVERAGE RATE: A five gallon pail will cover 300-375 sq. ft.

CLEAN-UP: Soap & water when wet, or orange citrus cleaner when dry.

PRECAUTIONS: KEEP FROM FREEZING. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: For limited warranty and disclaimer information, contact the Gardner corporate office at www.gardner-gibson.com.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0595-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	49 lbs.	1 ea.	025056059505

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101