

## 440 White Flash Pro White Roof Cement

- Repairs and Stops Leaks
- Fiber Reinforced Elastic Repair
- Non Sag, Heavy Duty Mastic

**Gardner® WHITE FLASH Pro White Roof Cement** is a heavy duty and highly flexible roof patching repair. **WHITE FLASH** is reinforced with synthetic fibers to deliver a durable and lasting repair. It is ideal to repair cracks and holes on a variety of roof surfaces. Perfect for use in hot climates as it does not sag in the high heat, and contains UV inhibitors for improved solar protection. Can also be used to seal metal seams, vertical walls and HVAC ductwork. Compatible with all white roof coatings.

**PREPARATION:** All surfaces need to be clean and dry. Best when applied early in the day to benefit from a full day of drying.

**APPLICATION:** Apply product with a trowel. Coat 2" beyond the entire damaged area, and then imbed reinforcing fabric. Trowel another layer on top to cover repair. Surface and air temperatures need to be 55 °F and rising. Do not apply if rain is expected within 6 hours.

**COVERAGE:** This pail will provide approximately 20 sg/ft of repairs.

**CLEAN-UP:** Clean tools with soap and water.

**PRECAUTIONS:** Protect from freezing. Protective clothing, gloves and eyewear should be used during application. During transport, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this will cause lid to loosen and leakage may occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT reuse empty containers. Do not use on EPDM, TPO, PVC or other rubber/synthetic or single ply roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Store unused product in a controlled environment, 55 °F - 80 °F. Do not store in direct sunlight.

**WARRANTY AND DISCLAIMER:** Gardner-Gibson, Inc. warranties this product to give satisfactory results when our directions are followed in its use and application, for a period of 7 years from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-4401	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	10.07 lbs.	4/crtn.	025056440167
SK-4403	3.5 gal.	11.9" x 11.9" x 10.5"	3.0 gal / 11.36 L	30.2 lbs.	1 ea.	025056440334