



031 Leak Stopper® Rubberized Roof Repair



- Stops roof leaks instantly
- Lasts 2-3x longer than other patches
- Fiber reinforced
- Flexes to prevent cracking
- Highest penetrating repair

DESCRIPTION: Leak Stopper® is a revolutionary advancement in roof patching and repair. This long lasting rubberized repair is specially formulated to penetrate deep into damaged areas and stop roof leaks instantly! The secret is Penetrex™, a unique penetrating oil that reaches deep into the crack and forms a complete seal. With the addition of liquid rubber, this flexible, high performance plastic cement provides a superior watertight bond that will stop problem leaks for good.

WHAT IT DOES: Stops roof leaks instantly.

WHAT IS NEEDED TO COMPLETE THE JOB? Trowel, gloves and reinforcing fabric.

PREP THE AREA: Surfaces must be clean, free of surface rust and loose material.

HOW TO APPLY: Use trowel to spread across damaged surface of roof. Embed reinforcing fabric after first layer and apply second layer on top of fabric.

HOW MUCH DO I NEED? Covers approximately 12 sq. ft. per gallon when applied 1/8" thick.

DO's and DON'Ts: Do apply in exterior applications only. Do wear protective clothing. Don't apply to plastic, EPDM, Hypalon or similar type of synthetic rubber roof system. If there is a question on compatibility, test a small section first before application to entire surface area.

FOR BEST RESULTS: It is highly recommended to reinforce the repair with a strip of Gardner Reinforcing Fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. DO NOT EXPOSE DIRECT HEAT/FLAMES OR THIN. Best used when surface temperatures are between 50° and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70 °F to 80 °F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round. Do not use on EPDM, TPO, PVC or other rubber/ synthetic surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Do not use in drinking water or food systems. KEEP FROM FREEZING.

HOW TO CLEAN-UP: Clean tools and spills with paint thinner or mineral spirits.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER- GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0319-GA	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1.3 lb.	12/crtn.	025056031907
0318-GA	1 qt.	4.4" x 4.4" x 5"	29 fl.oz. / 858 mL	2.3 lbs.	6/case	025056031808
0311-GA	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt / 3.4 L	9 lbs.	6/case	025056031105

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101