



2019-1-61 A2 Acrylic Latex Caulk

- Interior/exterior
- General use

Gardner® A2 is an acrylic latex caulk designed for general purpose sealing for interior or exterior applications. Use for caulking areas with no movement that will be painted over. Product is designed to be painted over.

Gardner® A2 may be applied on wood, brick, concrete, plaster, masonry, metal and drywall. It provides a reliable seal for seams around doors, paneling, windows, woodwork, baseboards and many other household surfaces.

How do I apply Gardner® A2?

1. Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease, oil and mildew. Apply the sealant when surfaces are clean and dry, and both the surface and the air temperatures are above 50 °F.
2. Trim nozzle to the desired bead size and load in caulk gun. While applying sealant, hold nozzle at a 45° angle, pushing sealant into the gap.
3. Sealant may be smoothed with a wet finger, sponge or brush. Important: When smoothing sealant, the remaining bead must be no smaller than 1/8" or larger than 1/2". When sealing larger cracks, a backing material must be used. Each tube covers approximately 55 linear feet per 3/16" bead.
4. Excess sealant can be cleaned up before it dries with a wet cloth. Use soap and water to clean up hands and tools.
5. This sealant can be painted over when dry, generally 6 to 8 hours, depending upon bead size and weather conditions. For best paint results during periods of high humidity and/or cool weather, an extended curing time may be required.
6. Do not caulk if rain or freezing conditions are anticipated within 24 hours of exterior application. Not intended for marine use, surfaces submersed in water or for repair of surface defects. Apply within one year of purchase.

CAUTION!: MAY CAUSE EYE AND SKIN IRRITATION. HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. Avoid breathing vapors, use only in a well ventilated area. Open doors and windows or use other means to ensure fresh air supply during application and drying. If overexposed, remove to fresh air and seek medical attention. Avoid contact with eyes or skin. In case of contact with eyes, flush with plenty of clean, room temperature water. Protective clothing, gloves and eyewear should be used during application of this product. Wash thoroughly after handling product. Seek medical attention if irritation develops. **DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40 °F.** Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. For the longest life, store in controlled environment, 40 °F to 80 °F. Do not store in direct sunlight. Do not allow product to freeze.

LIMITED 20-YEAR GUARANTEE: We guarantee that if you use **Gardner® A2 Acrylic Latex Caulk** as directed and it fails within 20 years of proper application, Sealant Technology will provide you with a free replacement cartridge. Return the used cartridge with your sales receipt to where the product was purchased for free replacement. This warranty applies for residential use only. Since it is impossible to control use and application of this product, Sealant Technology limits its warranty and liability strictly to replacement of product proven defective. No labor costs are applicable.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
2019-1-61	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz./ 296 mL	1.2 lbs.	12/case	758706201954

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101