

- Increases wet tack and slip
- Contains adhesive to increase bond
- Extends open time
- Great for pasting machines

**Dynamite 007 Pre-Pasted Wallcovering Activator** is ready to use and specially formulated to make installation of pre-pasted wallcovering easier, cleaner and trouble-free. Apply to the back of wallcovering to provide extra adhesion along with better slip and increased open time. This product provides the benefits to match patterns and butt seams more effectively.

**SURFACE PREPARATION:** Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use **Dynamite All-Purpose Cleaner** to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in the wall surface with **Dynamite Non-Shrink Spackling** prior to priming.

**Plaster** - New plaster must age at least 30 days before hanging wallcovering. Prime with **Dynamite 221** or **222**.

**Drywall** - New drywall must be wiped down with a damp cloth to remove dirt, grease, wax and peeling paint. Prime with **Dynamite 221** or **222**.

**Other Porous Surfaces** - Walls must be clean, dry, smooth and structurally sound. Prime with **Dynamite 221** or **222**.

**Glossy Surfaces** - Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica<sup>®</sup>, glass, plastic or baked enamel should be primed with **Dynamite 221, 222** or **235**.

**DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.**

**APPLICATION:** Mix well before using to ensure even consistency. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to the manufacturer's hanging instructions. IMMEDIATELY remove adhesive from the face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Hang wallcovering according to the manufacturer's hanging instructions.

**COVERAGE:** 5 gallons will hang up to 50 single rolls (1750 sq. ft.). Coverage rate can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

**CLEAN-UP:** Cleans with water.

**QUALITY PROMISE:** Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7007-3-20	1 gal.	7.625" x 7.625" x 7.875"	3.6 qt. / 3.8 L	9 lbs.	4/case	027134700729
7007-3-30	5 gal.	12.5" x 12" x 14.75"	4.75 gal. / 18.9 L	42 lbs.	1 ea.	027134700736