

- Superior wet tack and slip
- Longest open time
- Stir to desired consistency
- Ideal for pasting machines
- Strippable

Dynamite[®] 234 Premium Grade Heavy Duty Clear Wallcovering Adhesive is recommended for hanging lightweight to heavyweight vinyl and foil wallcoverings. It is also excellent for hanging delicate and difficult wallcoverings such as silks, suedes, velours, linens, burlap, grasscloth and strings.*

*FABRICS, FOILS, STRINGS, GRASSCLOTH AND SILK – When hanging delicate wallcoverings, special care must be taken in keeping the adhesive off the face of the wallcovering as it may cause permanent discoloration. It is recommended that a sample of the selected wallcovering be tested for degree of stain resistance prior to the installation. Some wallcovering can be stained by water alone.

SURFACE PREPARATION: Make sure wall surface is sound, clean and dry. Use an all-purpose phosphate-free cleaner to prepare walls. A diluted household bleach solution works well to clean walls. After cleaning rinse wall with clean water and allow to dry. Repair or fill cracks in wall with Dynamite Non-Shrink Spackling prior to priming.

Plaster – New plaster must age at least 30 days before hanging wallcovering. Prime with Dynamite 221 or 222.

Drywall – New drywall must be wiped down with a damp cloth to remove dust, dirt and grease. Prime with Dynamite 221 or 222.

Other Porous Surfaces – Walls must be clean, dry, smooth and structurally sound. Prime with Dynamite 221 or 222.

Glossy Surfaces – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica[®], glass, plastic or baked enamel should be thoroughly cleaned and then primed with Dynamite 221, 222 or 235.

Commercial Grade Type II & III – Prime with Dynamite 235 when hanging heavyweight commercial grade wallcovering. Allow primer to dry 24 hours before hanging wallcovering.

Strippability – No primer is needed when hanging strippable, fabric-backed vinyl wallcoverings. Adhesive and primer (if used) must be completely cured prior to stripping. **DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.**

APPLICATION: Hang wallcovering according to manufacturer's hanging instructions. Stir to thin paste to desired consistency. **Do not dilute.** Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. **Immediately** remove adhesive from the face of washable wallcoverings and adjacent surfaces with a clean, wet sponge.

COVERAGE: Five gallons of adhesive will hang up to 40 single rolls. (1,400 sq. ft.) Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions, and method of application.

CLEAN-UP: **Immediately** remove adhesive from the face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

PRECAUTIONS: **Premium Grade Heavy Duty Clear Adhesive** should be stored at temperatures between 40 °F and 100 °F. **KEEP FROM FREEZING.** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Do not use in drinking water or food systems.

QUALITY PROMISE: Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. This limited warranty is in lieu of all other express or implied warranties, including the warranties of merchantability and/or fitness for any particular use or purpose and Gardner-Gibson, Inc. will in no

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7234-3-20	1 gal.	7.625" x 7.625" x 7.875"	1 gal. / 3.79 L	10 lbs.	4/case	027134723421
7234-3-30	5 gal.	12.5" x 12" x 14.75"	5 gal. / 18.9 L	50 lbs.	1 ea.	027134723452