

- Excellent tack, strong bond
- Extremely resistant to high humidity
- Needs no primer
- Great for pasting machines

Dynamite[®] 760 Vinyl Over Vinyl Wallcovering Adhesive is specially designed for installing vinyl or foil wallcoverings over existing vinyl wallcoverings and other difficult surfaces. **Dynamite 760** is also used for installing all types of borders over existing wallcoverings and other difficult surfaces. This product cleans up with water while wet.

PREPARATION: Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use **Dynamite All-Purpose Cleaner** to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in wall with **Dynamite Non-Shrink Spackling**. No priming is required with this Dynamite adhesive product.

APPLICATION: Mix well before using to ensure even consistency. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. **NOTE:** When hanging pre-pasted borders, dampen back of border with wet sponge. Wait 2 minutes, then apply Border Over Vinyl in a thin, even coat to the back of the border. This prevents over-absorption of the paste. Strip should be booked for 5 minutes prior to hanging. **IMMEDIATELY** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge.

COVERAGE: Five gallons will hang up to 40 single rolls (1400 sq. ft.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

PRECAUTIONS: **Vinyl Over Vinyl Wallcovering Adhesive** should be stored at temperatures between 40 °F and 100 °F. **PROTECT FROM FREEZING.** For longest life, store in controlled environment, 55 °F-80 °F. Do not store in direct sunlight. Do not store/warehouse product below 32 °F for extended periods of time. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Do not use in drinking water or food systems. Keep container closed when not in use.

QUALITY PROMISE: Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. **THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7760-3-16	1 qt.	5.125" x 5.125" x 4.875"	1 qt. / .946 L	2.5 lbs.	6/case	027134776038
7760-3-20	1 gal.	7.625" x 7.625" x 7.875"	1 gal. / 3.79 L	9.5 lbs.	4/case	027134776014
7760-3-30	5 gal.	12.5" x 12" x 14.75"	5 gal. / 18.9 L	47 lbs.	1 ea.	027134776021