

- Stops leaks!
- Long lasting flexible repair
- Use with reflective coatings
- Use with reinforcing fabric

**Sta-Kool® 390, White Acrylic Sealant Flexible Roof Patch** is an extra tough, flexible repair compound designed to patch splits, cracks and holes in roof surfaces. This water-based patch dries quickly to a non-tacky surface which offers great adhesion to all coatings applied over it. It is designed to repair cracks and holes up to 1" in width. **Sta-Kool® 390** should be used with **Universal Patching Fabric**. **Sta-Kool® 390** remains flexible while it expands and contracts with your repair, making it ideal to use with all **Sta-Kool®** products.

**PREPARATION:** All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Rusty metal must be cleaned with a wire brush and primed with a suitable primer before application of this product. Washing entire surface is recommended for best results. Surfaces with mildew growth or stains must be cleaned with a bleach solution (2 parts water to one part bleach) prior to applying this product. Be certain all surfaces are thoroughly rinsed and dry prior to applying patching material.

**APPLICATION:** For best results, apply in early morning hours on clear sunny day. Surface and air temperatures must be a minimum of 65°F and rising. DO NOT apply if heavy dew or rain is expected within 24-48 hours. Apply with a stiff bristled paint brush. Coat entire damaged area and extend 2" beyond damaged area. Embed Universal Patching Fabric into the repair while wet. Apply second layer of patch, brushing over and into embedded fabric. Allow to cure 24-48 hours and coat entire roof with a **Sta-Kool®** reflective roof coating. DO NOT THIN. If roof becomes hot (over 100° F) during application, lightly mist roof surface with water spray to prevent coating from drying too fast. Remove any excess or puddling water prior to coating. If roof surfaces become soiled with age, due to the elements, **Sta-Kool® 390** can be cleaned with a mild solution of bleach and water. Excess scrubbing should be avoided. If coloring is desired, a typical addition of 3-4 ounces per gallon of Universal colorant can be added, which will result in light pastel colors. Note: Color tinting will disclaim warranty.

**COVERAGE RATE:** Approximately 25 sq. ft. per gal.

**CLEAN-UP:** Clean tools with soap and water.

**PRECAUTIONS:** DO NOT allow product to freeze. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and can secure and upright. Do not allow can to tumble as this may cause lid to loosen and leakage to occur. DO NOT transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT store at temperatures above 100°F. DO NOT reuse empty containers. Close container after use. Do not use in drinking water or food systems. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. For longest life, store in controlled environment, 35°F-80°F. Do not store in direct sunlight.

**WARRANTY AND DISCLAIMER:** For limited warranty, MSDS and disclaimer information, contact the Gardner corporate office at [www.gardner-gibson.com](http://www.gardner-gibson.com).

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-3909	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1 lbs.	12/crtn.	025056390967
SK-3901	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	12.3 lbs.	4/crtn.	025056390165

[www.gardner-gibson.com](http://www.gardner-gibson.com)  
**Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449**  
**Phone: (813) 248-2101**