



## STANDARD FEATURES

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- RS-232 serial communication

*Note: Does not support double-strike commands.*

## SPECIFICATIONS

### Print Speed:

1.9 to 2.3 lines per second (5 × 7 character, 3 dot line spacing)

### Column Capacity:

35/42 columns

### Characters Per Line:

35 standard font

### Print Area:

2.59 in W (65.8 mm W)

### Character Formation:

5 × 7 and 7 × 7 dot matrix

### Character Height:

0.11 standard font

### Character Set:

Full 96-character ASCII; with software control, 32 international characters, 128 × 2 graphic characters

### Line Spacing:

0.16 in (4.06 mm) software programmable in 1/60 in units

### Print head Life:

Approximately 100 million strokes/pin

### Form Thickness:

Single-ply: 0.003 to 0.009 in (0.08 to 0.23 mm)  
Copy paper: 0.003 to 0.014 in (0.08 to 0.36 mm)

### Ribbon:

Cassette-type purple ribbon

Ribbon life is approximately 1.5 million characters (continuous prints)

Black ink also available

### Serial Interfaces:

RS-232 (DB-25F) compatible

Baud Rates:

1200, 2400, 4800, 9600, selectable

### Parity:

7 or 8 bits, none, even or odd

Stop Bits:

1 or more

### Handshaking:

DTR/DSR or XON/XOFF control selectable

### Overall Dimensions:

(L × W × H)

7.49 × 7.08 × 3.99 in

(190.5 × 180 × 101.5 mm)

### Weight:

9 lb

### Warranty:

One-year limited  
(includes print head)