

Removable Wall Decal Installation Instructions

STOP! PLEASE READ BEFORE USING

If you have any questions about the proper installation of this product, please call your Distributor or contact your Sales Representative before proceeding.

PREPARATION OF PRODUCT

Examine goods to assure that pattern, color, quantity and quality are as ordered.

PREPARATION OF SURFACE

Surfaces to be covered must be clean, smooth, dry and structurally sound. Loose paint or other wallcoverings must be removed. In order to ensure maximum smoothness of installation, nail heads, nicks, gouges and other surface imperfections should be filled, sanded smooth and sealed. On new walls, drywall joints should be taped, bedded and sanded smooth. If necessary, clean the surface with a damp cloth and allow it to completely dry.

APPLICATION OF WALL DECAL

Peel back approximately 2-3" of the backer and crease it to leave the sticky surface exposed. Place the 2-3" of exposed sticky surface on your wall as desired and take your time sticking it evenly across. Apply the rest of the decal by slowly peeling the backer downward while at the same time smoothing the material onto the wall. Working from the center outward, gently smooth out any wrinkles with a plastic putty knife.

CONSIDERATIONS

This product is not designed to be used on textured surfaces, and you should avoid placement above fireplaces or furnaces. Allow 30 days for newly painted walls to dry before applying.

Depending on the size of your Print4One product it may be easiest to have another person help install it. If necessary, you can peel this product off and reposition it accordingly. You can remove and reuse this product multiple times as long as the adhesive side doesn't collect dust or debris.

Do not install wall decals unless a temperature above 55°F is maintained in both areas of installation and storage..