


Assembly Directions for Vinyl A-Frame

#VAF920



To avoid personal injury or damage to your A-Frame, assembly requires two people.

NY-GUIDE™
Swing Connector Installation

The swing connector has been engineered to screw into a 9/32" pilot hole, 2 1/2" deep. It is designed to pivot from the front to the back of the swing set. The triangular bend of the screw-eye must end up tightly against the rail in a parallel position.

NOTE: Use a screwdriver for leverage while turning.

NOTE: The manufacturer can assume no responsibility for the incorrect installation of the NY-GUIDE™ Connectors.

NOTE: NY-GUIDE™ pivots perpendicular to the ladder rail.

Screw into the wood all the way up to the bend of the neck or breakage. RESULTING IN INJURY, can occur.

PACKAGE CONTENT

1 Top Beam	2 Long Leg Braces
4 Legs	4 Top Braces
2 Short Leg Braces	1 Hardware Package

HARDWARE PACKAGE

2 3/8" x 7 1/2" Machine Bolts	2 5/16" Washers
2 5/16" x 5 1/2" Machine Bolts	2 5/16" Flange Nuts
20 1/4" x 4" Lag Bolts	20 1/4" Washers
4 3/8" Washers	2 3/8" NY Glides
2 3/8" Nuts	2 Vinyl Hole Plugs

TOOLS NEEDED:

Hammer, 1/2" Wrench,
7/16" Wrench, 9/16" Wrench,
& Screw Gun



Step #1
Fasten legs using $\frac{3}{8}$ " x $7\frac{1}{2}$ " Machine Bolts (on both sides of swing). **Note:** Two of the legs will have five (5) predrilled holes (see inset). Make sure one of these legs is located on each end of structure.



Step #2
Tighten Nuts using a $\frac{3}{8}$ " socket and cordless drill.




Step #3
A. Line up Braces with the predrilled holes and fasten using $\frac{1}{4}$ " x 4" Lag Bolts with a Washer.
B. In the event that your A-Frame does not include a Vinyl A-Frame Roof, insert the two Vinyl Hole Plugs into the extra predrilled hole.



Step #4
Stand up your A-Frame as shown.




Step #5
Fasten the Top Braces to the Top Beam using $\frac{5}{16}$ " x $5\frac{1}{2}$ " Machine Bolts and $\frac{5}{16}$ " Washers & Flange Nuts.



Step #6
Fasten the Short Leg Brace to the Top Brace using $\frac{1}{4}$ " x 4" Lag Bolts (and $\frac{1}{4}$ " Washer). As shown in the inset, ensure that the bottom of the Short Brace is even with the bottom edge of the Top Brace.



Step #7
Install the NY Glides.

 **To avoid personal injury or damage to your A-Frame, assembly requires two people.**