

FRP Fiberglass Reinforced Plastic Grates

Product Description/Use:

Raise floors featuring artificial turf, rubber flooring or other non weight bearing surfaces require additional substrate support. Our FRP (Fiberglass Reinforced Plastic) panels install over our pedestal systems, providing a structural floor to lay deck turf as well as wood deck tiles, porcelain pavers, concrete pavers or any other exterior floor desired. These lightweight grated panels provide unparalleled performance to allow mixed flooring materials to be used seamlessly in any application including pool surrounds, outdoor terraces, rooftop decks, patios, balconies and other exterior areas



Product Details							
Sizes	24"x24"x1"	24"x48"x1"	24"x48"x1.5"				
Open Area	3/4"x3/4"	3/4"x3/4"	3/4"x3/4"				
Open Area	44%	44%	44%				
Surface Texture	Sanded grip	Sanded grip	Smooth				
# of Bars/ Ft of Width	8	8	8				
Load Bar Width	1/4"	1/4"	1/4"				
Load bar Centers	1-1/2"	1-1/2"	1-1/2"				
Weigth	2.9 lb/SqFt	2.9 lb/SqFt	2.9 lb/SqFt				
Additional Specs	Meets Army Corps of Engineers Guidelines						
	ADA Compliant						
	Corrosion Resistant						

Composition Information						
Chemical Component	CAS Number	Percent				
Polymerized Resin	None	30%-75%				
Fiberglass	65997-17-3	25%-70%				
Quartz Silica Sand (Present Within Anti-Slip Gritted Products Only)	14808-60-7	1%				
Fire Rating	spread ratin	g < 25				

Uniform Load Table - Deflection in Inches

Clear Span (in)	Depth	LOAD (psf)							Maximum Rec. Load (psf)	Ultimate Load (psf)		
		50	65	100	150	200	300	500	1000	2000		
24	1"	0.04	0.05	0.08	0.12	0.16	0.24	0.41		<	440	2220
24	1-1/2"	0.02	0.03	0.04	0.06	0.06	0.12	0.21	0.42		510	4000
48	1-1/2"	0.28	0.37					\	}-		120	1000