

## Product Description/Use:

Porcelain paver tiles are one of the best options for rooftop flooring and other exterior raised floors due to their exceptional durability, weather resistance, and aesthetic appeal. Our Porcelain Pavers come in a wide variety of shapes and finishes including natural stone, concrete, terrazzo and wood looks. Made from high-quality porcelain in a robust 2 cm thickness, they are designed specifically for outdoor use, making them a popular choice for rooftop decks, patios, terraces, walkways, and pool decks.



### Underside



Pedestal Installation Method

| Product Details        |                                  |
|------------------------|----------------------------------|
| Primary Size (All)     | 24"x24"                          |
| Other Sizes Available  | By SKU (see website for details) |
| Overall Tile Thickness | 20 mm                            |
| Material               | Rectified Porcelain              |
| Overall Tile Weight    | 9 lbs/SqFt                       |

| Test Results                          |                     |                      |            |
|---------------------------------------|---------------------|----------------------|------------|
| Spec                                  | Test                | Standard             | Result     |
| Water absorption *                    | ASTM C-373          | ≤ 0.5%               | Passed     |
| DCOF: dynamic coefficient of friction | ANSI A326.3         | ≥ 0.42               | Compliant  |
| Resistance to freeze/thaw cycling     | ASTM C1026          | As reported          | Resistant  |
| Chemical resistance                   | ASTM C-650          | As reported          | Unaffected |
| Thickness                             | ASTM C-499          | ± 1.5 mm (± 0.06 in) | Compliant  |
| Breaking strength                     | ASTM C-648 / C-1505 | 250 lbf or greater   | ≥2200 lbf  |
| Warpage (edge)                        | ASTM C-485          | ± 0.4% or ± 0.05 in  | Compliant  |
| Warpage (diagonal)                    | ASTM C-485          | ± 0.4% or ± 0.07 in  | Compliant  |
| Wedging                               | ASTM C-502          | ± 0.25% or ± 0.03 in | Compliant  |
| Facial dimension                      | ASTM C-499          | ± 0.25% or ± 0.03 in | Compliant  |
| Resistance to thermal shock           | ASTM C-484          | Pass                 | Compliant  |
| Resistance to stain                   | ASTM C-1378         | As reported          | Resistant  |