

#### **CODE NUMBER**

3325403

#### **DESCRIPTION**

0.5 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Battery, G2 Exposed Sensor Urinal Retrofit Flushometer.

#### **DETAILS**

Flush Volume: 0.5 gpf (1.9 Lpf)
Finish: Polished Chrome (CP)
Power Type: Battery ()
Battery Life: 6 years

Valve: Diaphragm

• Valve Body Material: Semi-red Brass

• Fixture Type: Urinal

• Fixture Connection: Top Spud

#### **FEATURES**

• User friendly three (3) second Flush Delay

• "Low Battery" Flashing LED

 Infrared Sensor with Multiple-focused, Lobular Sensing Fields for high and low target detection

 Flex Tube Diaphragm designed for improved life and reduced maintenance

• Engineered Metal Cover with replaceable Lens Window

 Diaphragm to be molded from PERMEX™ Rubber Compound for Chloramine resistance

• Courtesy Flush® Override Button

• Handle cap included

• Four (4) Size AA Batteries included



### **COMPLIANCES & CERTIFICATIONS**













(ADA Compliant, BAA Compliant, BREEAM Water Credit, cUPC Certified, cUPC Green Certified, Green Globes Water Credit, Satisfies LEED Credits)

#### RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

### **ELECTRICAL SPECIFICATIONS**

• Battery Life: 6 years

# **VALVE OPERATING PRESSURE (FLOWING)**

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

# **DOWNLOADS**

- Optima Plus Valve Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Additional Downloads

### **NOTES**

All information contained within this document subject to change without notice.

Looking for other variations of the G2 RESS-U product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.



# **ROUGH-IN**



