

Pure Blue

Dual Stage Drinking Water Filtration System

This is for the set of PRE and POST replacement filters for the Pure Blue Dual Stage Drinking Water Filtration System. It is recommended that these filters be changed out every six months to a year to ensure the highest quality filtration.

Dual Stage Filter Change Instructions

Preparation

*Place either towels or paper towels directly underneath the system to catch any remaining water.

*The Pre and the Post filters for the Pure Blue Dual Stage Drinking Water Filtration System may be the same type of filter, depending on your purchase. If there is no designation ON the filter as to which is PRE and which is POST, then they are both the same filter and there is no designation.

*Remove the yellow cap from the new filters before you begin

Shut off the water

a. Locate the shutoff valve for the **FEED** and turn it **OFF**.

2) Release the pressure in the system

- a. Open the spigot until it stops dripping.
- b. Close spigot when the drip stops.



3) Remove the Old Filters

a. REMOVE the filters by turning it CLOCKWISE until all filters are clear of the manifold.

4) Install the New Filters

- a. INSTALL the new filters by placing it in the slot and tightening COUNTER-CLOCKWISE until hand tight.
- b. After the filters are installed properly, OPEN the spigot (see image on step 2), then OPEN the feed (see image on step 1).

5) Begin the flushing procedure

- a. With the spigot ON, and the filters installed, turn the FEED back ON.
- b. Once proper flow has been confirmed, turn the spigot back OFF.
- c. Let the system pressure up for 10 minutes, checking thoroughly for any leaks.
- d. If no leaks have been detected after 10 minutes under pressure, **OPEN** the spigot, and complete the final flushing procedure.

6) Final Flush

- a. Let the system run open for 10 minutes, in order to flush out the new filter. After 10 minutes, close the spigot, and check the cabinet again for any excess moisture.
- b. Your Pure Blue Dual Stage Drinking water system is ready to be used again!

^{**}Following a filter change, the water from your spigot may appear slightly cloudy due to air remaining in the system. This water is completely safe to drink and will return to normal clarity within a few days. For any issues regarding filter changes, please reach out to our Technical Support department at (877) 534-5837 ext. 7

