

iFUEL® CUBE

110% Self Bunded Tank Range

Suitable for the Transport, Storage and Dispensing of Diesel, Lubricants, Kerosene and Petrol.

- True 110% Self Bunded Tank, Fully Baffled.
- 110% Tank In Tank Design. The primary tank can be removed from the secondary tank for cleaning and maintenance, over time.
- Designed and approved for the storage and transport of diesel, petrol, lubricants and waste oil
- Mild Steel Internal Tank and Wetted Parts - Heavy duty mild steel External tank.
- Pumps / connections / hoses / meters and filters can be housed in the bunded area of the tank, which can be locked even when in use!
- Stackable - 3-high empty / 2-high when full. UN31AY Designed and Approved for the transport of dangerous goods up to and including 3300L.
- Designed and approved to AS1940 and AS1692 for static storage applications.
- Easily removable carbon steel inner tank for maintenance and cleaning.



2200L CUBE-2200 fitted with electric start, diesel driven dispensing package.

PRODUCT RANGE

| | CUBE-550 | CUBE-1100 | CUBE-2200 | CUBE-3300 | CUBE-4500 | CUBE-6300 | CUBE-8000 |
|-------------------|----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Capacity | 550L | 1100L | 2200L | 3300L | 4500L | 6300L | 8000L |
| Safe Fill Level | 500L | 1000L | 2000L | 3000L | 4100L | 5950L | 7600L |
| Length (mm) | 1509 | 1577 | 1589 | 2180 | 3000 | 3560 | 4600 |
| Width (mm) | 1114 | 1132 | 2166 | 2166 | 2000 | 2166 | 2246 |
| Height (mm) | 796 | 1235 | 1221 | 1221 | 1235 | 1235 | 1235 |
| Weight Empty (kg) | 450 | 680 | 980 | 1139 | 1650 | 2450 | 2880 |
| Weight (kg) | 950 | 1680 | 2680 | 3840 | 5175 | 7205 | 9500 |