

HOW TO APPLY

&
Maintenance Tips

Uploaded by www.lizardgrip.in

LizardTM Grip

ANTI-SLIP FLOOR SOLUTION

www.lizardgrip.in

Lizard Grip is extremely easy to apply and can be done by any member of the household. However certain precautions must be maintained.

- Do not apply in direct sunlight and provide enough ventilation.
- Do not use any electronic dryer to dry.
- Please ensure that all your water sources are completely shut, until the LIZARD GRIP Anti Slip Floor Solution application process is complete.
- Do not use the floor during floor treatment time.
- Use gloves and footwear during application.
- Keep out of reach of children.

STEP 1

Solution 1

Dilute the given Floor Degreaser in 200 ml water. Now spread this mixture on the floor and leave it for 5 mins. After 5mins scrub and clean the floor so that it is free from all kinds of dirt and protein molecules. To scrub the floor use a hard plastic bristles deck brush.

STEP 2

Wipe the water with wiper. The floor should be damp not completely dry but there should not be any trace of water droplets.

STEP 3

Solution 2

Now apply Lizard Grip Anti Slip **Solution - 2** and spread it evenly on the floor with the non-abrasive applicator included in the pack and leave it for 30 minutes. While spreading the anti-slip floor solution use vertical and horizontal movements. After 10 minutes rub the floor again with the applicator for 2-3 minutes using vertical and horizontal movements.

Note: Don't pour the anti slip solution directly on the floor. Pour the content of the bottle in a plastic/non metallic tray. Dip the given applicator in the anti slip solution and spread it evenly on the floor using vertical and horizontal movements.

NOW YOU ARE SAFE FROM SLIP FALL ACCIDENTS, THANKS

BEFORE APPLYING ON THE ENTIRE AREA PLEASE TEST THE SOLUTION IN A SMALL TEST AREA.

While applying the solution you will find foam or lather being generated. This is normal.

The ingredients in the pack are adequate for anti slip treatment of floor area up to 60 sq ft.

STEP 4

After 30 minutes pour plain water on the floor and scrub the floor clean with the given non-abrasive pad. Use adequate water to clean the floor thoroughly. No anti slip solution should be left on the floor.

STEP 5

Solution 3

Once step 4 is complete remove the excess water from the floor using a rubber squeeze and pour the content of Lizard Grip Anti Slip **Solution - 3** and spread it evenly on the floor using the given applicator pad. Leave the anti slip solution of the floor for 2-3 minutes.

Note: While applying the second treatment you should not make the floor completely dry and leave it slightly damp. Also wash the applicator pad well so that there is no anti slip solution of Treatment 1 left in the pad.

STEP 6

After 2-3 minutes pour plain water on the floor and scrub the floor clean with the given non-abrasive pad. Use adequate water to clean the floor thoroughly. No anti slip solution should be left on the floor.

Example: If you have two bathrooms of 30 sqft each then divide the contents into to two parts and use one part per bathroom.

TO LIZARD GRIP ANTI SLIP. WALK WITH CONFIDENCE.

Testing the anti-slip floor

- a. Try sliding your feet with enough pressure (full body weight) and compare it with an untreated surface. The weight should be similar to when you stand on the floor. Please note that the anti-slip properties come into effect when the full body weight falls on the floor just like under normal conditions. If you run your palm or finger lightly on the floor you will not feel the anti-slip property.
- b. In dry conditions, you will not feel the difference but once you pour water you will find the friction after couple of inches of sliding of your feet or palm. The sliding property has been deliberately engineered into the solution so as to avoid a sudden braking effect and prevent a person from falling on his/her face.

Maintenance Procedure

Effective and regular cleaning of the floor is extremely important to keep the anti-slip/anti-skid effect active. Use hard plastic bristle deck brush to clean the floor twice a week. Frequency depends on contamination and footfall. Extremely heavy footfall areas may require everyday cleaning.

Only mop cleaning will reduce anti slip effect overtime. Scrub cleaning using hard plastic bristle deck brush is mandatory.

Grip Kleen Anti Slip cleaner and track restorer should be used once in every 30 days to keep the warranty clause applicable.

After the LIZARD GRIP Anti Slip treatment, there are minor stipulations for all surfaces.

They are as follows:

1. No waxing, coating, painting, sealing or grinding of any kind on the surface. This will permanently cover up the suction cups created into the surface.
2. No metal wire brushes allowed in cleaning of treated surfaces. Plastic bristles or big machines with plastic bristles are acceptable.
3. No usage of acidic cleaning substances like Harpic Blue, Hydrochloric Acid, Sulphuric Acid and so on.

Recommended Cleaner for Regular Cleaning

Highly alkaline cleaner with deep clean ability like **Sharp Kleen** or equivalent.