Mammoth Ligh Box

Instructions



Step 1: Start by placing the light strips on the inside groves of both sides of the Mammoth Frame. Place the strips so that the "male" connections are on the bottom of the light strip with the "female" connections at the top of the light strip.



Step 2:

If you placed the strips correctly, see step one to read the correct placement, then connect the strips together by inserting the male connection into the female connection. *NOTE: Due to the size* of your display you may an extra "female" connection.



Step 3: Take out two "male' and "female" transformer connections. (recognizable by their red connectors). At the bottom of the either side of the frame you will find a hole. Put the female parts on the inside of the frame and the male parts outside of the frame. Connect red to red, and black to black. Secure the connection by pinching the end caps with tools.



Step 4:

When you are finished with Step 3 you should have two completed transformer connectors passing through the hole at the base of the side panel of the frame.



Step 5:

Find the longest connection cord in the displays package. This cord will be used to connection the strips on the other side of the frame to the transformer. Place this cord on the inside of the bottom part of the frame along the center grove. Connect it to the set of strips on the other side of the frame.



Step 6:

Connect the transformer connectors for both sets of strips to the transformer, plug the transformer in, and turn it on. You will know the transformer is working properly if the fan is active and rotating. The lights should come on as soon as the transformer is turned on.