

DESCRIPTION

467 is a 27# / 100gsm durable, lightweight, tear resistant paper. The patented manufacturing process creates a tear resistant, layflat sheet that tracks well through roll and sheet fed inkjet and toner devices without static or curl. The paper surface provides compatibility with multiple inkjet and toner devices.

PHYSICAL CHARACTERISTICS

Caliper	4.5 mil
Basis Weight	100 gsm
Bond Weight	27#
Brightness	92%
Finish	Matte
Opacity	92%
Whiteness	NA
Smoothness	120
Lab Values	NA
Base material	Paper / Film / Paper
Structure	Uncoated

*All values are for reference only

FEATURES AND BENEFITS

- Good print performance
- Good toner / ink adhesion
- Good line acuity
- Good image sharpness
- Good black density
- Smooth matte finish

COMMON APPLICATIONS

- Maps
- Menus
- Labels / Packaging
- Tickets
- Renderings / Drawings
- Charts
- Certificates

PRINTER COMPATIBILITY

- WF Toner** - KIP / Oce / Xerox
- Aqueous Dye** - Epson / Canon / HP
- Aqueous Pigment** - Epson / Canon / HP
- Pagewide** - HP
- Memjet** - Oce / Fuji - Xerox / RTI / Xante
- Latex** - HP / Mimaki
- Toner Press** - Canon / Konica Minolta / Xerox / Ricoh
- UV** - Fuji / Agfa / CET / HP / Oce / Mimaki / Vutek

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- PageWide ink can take up to 24 hours to cure.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.
- Can use pen / pencil to write on surface
- Compatible with common stapling and binding equipment

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature	72° F
Relative Humidity	42-50%

OPTIMAL SERVICE ENVIRONMENT

Temperature	72° F
Relative Humidity	42-50%

