

# 8 Mil Satin Photo Paper



This bright white production photo paper offers vivid colors and great contrasting blacks. The instant-dry microporous coating generates an efficient work flow, allowing you to handle the prints immediately without creating any smudges or fingerprints. After a short period of extra drying time you can laminate this material using pressure-sensitive or low-heat thermal laminates. Printing high-volume quantities with these photo papers is easy since they are compatible with any aqueous printer that uses dye or pigment ink. The natural satin finish helps the colors really pop without the risk of glare when prints are displayed under bright lights.

Benefits	Applications	Customers
<ul style="list-style-type: none"><li>• Wide color gamut allows for vivid colors</li><li>• Cost effective</li><li>• Instant-Dry coating for high volume production</li><li>• Compatible with dye and pigment inks</li></ul>	<ul style="list-style-type: none"><li>• Proofing</li><li>• Photo printing</li><li>• Posters</li><li>• Short term signage</li></ul>	<ul style="list-style-type: none"><li>• Commercial offset printers</li><li>• Photo printers</li><li>• Framing shops</li><li>• Digital photographers</li><li>• Fine Art reproduction houses</li></ul>

**SPECIFICATIONS**

Material Type	Resin-coated photo paper
Gauge	8 mil
Applications	Photo reproductions, posters
Product Benefits	Instant-dry, cost effective
Weight	190 gsm
Finish	Pressure-sensitive or thermal laminates can be applied to increase the fade- and abrasion-resistance of the image. Before applying the laminate, allow the image to dry for 24 hours.
Whiteness	143% (CIE)
Opacity	95%
Gloss Level	17%
RIP & Printer Media Settings	For the best and most consistent results, a profile should be created using a calibrator in conjunction with your RIP and color matching software. If custom profiles are not available, try a few different on-board media settings to achieve optimum performance.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Please consult with your ink manufacturer for light fastness data.
Water Resistance	Water-resistant with aqueous pigmented inks.
Optimal Service Environment	60 - 86° F, 50% Relative Humidity.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Color	L 95.3 ± 0.5 a -0.9 ± 0.4 b -1.9 ± 0.6 delta b 10.5 ± 1.
Ink Compatibility	Dye and pigment-based aqueous inks
Shelf Life	1 year from the ship date when stored in proper conditions.

SKU	Size
SSP82400	24" x 100 ft.
SSP83600	36" x 100 ft.
SSP84200	42" x 100 ft.
SSP85000	50" x 100 ft.
SSP86000	60" x 100 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.