



.006 White Static Cling 8pt Tag
MGX-4207
13" x 19"

Superior ink and window adhesion properties.

TYPICAL APPLICATIONS

- Window Decals and Graphics
- Learning Tools and Game Pieces
- Promotional and Temporary Displays
- Protective Film
- Indoor P.O.P. Graphics

PRODUCT SPECIFICATIONS

Standard Gauges	6-mil
Surface Energy	32-36 dyne/cm
Minimum Application Temperature / Service Temperature	40° F / 0° F - 175° F
Dimensional Stability (at 100° C)	>8%
Tensile Strength (MD/TD)	2300 min. / 2200 min.
Gloss Level	150 +/- 25
Light Transmission/Haze (Clear Only)	~90% / ~10%
Liner Options	8-pt

Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind. All purchasers of MGX products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of MGX is authorized to give any warranty, guarantee, or make any representation in addition or contrary to the above.