


WING Series 4FT LED Architectural Suspended Linear Light

| ITEM | Product specification | | File No: LL40W345K8-HB-BK-4R A1 | |
|---|---|-----------------------------|---|-----------------------|
| | | | STATE:ACTION | PAGE: 1 |
| Commodity | North American Wide Voltage Economy Linear Light 3000K/4000K/5000K | |  | |
| Series name | Led Linear Light | | | |
| Specifications model | LL40W345K8-HB-BK-4R | | | |
| Description : Using high-quality Aluminum material, good stability, high reliability, energy saving, easy to install , environmental protection, high grade and beautiful | | | | |
| Use : Corridors, washing rooms, corridors, schools, hotels, museums, jewelry stores, shopping malls, office buildings, etc. | | | | |
| Parameter | | | Unit | Data |
| Electrical Characteristics | 1 | Rated Wattage | W | 40 |
| | 2 | Input Voltage | V | 120-277V |
| | 3 | Rated Frequency | Hz | 50/60 |
| | 4 | Driver Output current | mA | 1050 |
| | 5 | Power Factor | | 0.95 |
| Light data Color data | 6 | Luminous flux | Lm | 4800 |
| | 7 | Lumen Efficiency | Lm/W | 120 |
| | 9 | Light angle | ° | 120 |
| | 10 | 3000Hours Lumen Maintenance | % | 92 |
| | 11 | Color temperature | K | 5000 |
| | 12 | Color rendering index(Ra) | | 80 |
| Other | 13 | Rated life | Hrs | 50000 |
| | 14 | Length L | inch | 45 |
| | 15 | Breadth B | inch | 2.6 |
| | 16 | Height | inch | 2.8 |
| | 17 | Base | / | / |
| | 18 | Weight | kg | 2.24 |
| | 19 | Dielectric Strength | V | 1500 |
| | 20 | Electric shock proof grade | | Class I |
| | 21 | LINKABLE | | Y, Max 6 units |
| | 22 | accord with ETL(Y/N) | | Y |
| | 23 | Work environment | | 0%~80% R.H;14°F~104°F |
| | 24 | Storage environment | | 0%~85% R.H;14°F~130°F |
| | 25 | Protection grade | | IP22 |
| | 26 | Installation mode | | Hanging |
| Package | 27 | Four pieces for master box | inch | 47*7.9*8 |

WING Series 4FT LED Architectural Suspended Linear Light

File No: LL40W345K8-HB-BK-4R A1

ITEM

Product specification

STATE:ACTION

PAGE: 2

- 1、 In order to ensure the normal operation of the product, please ensure that the voltage used in the working voltage range.
- 2、 Please disconnect the power supply when installing and disassembling products to avoid the risk of electric shock.
- 3、 in order to ensure the effect, please do not use this product in high humidity or dusty environment, including but not limited to the following environment: bathroom, sauna room, grinding workshop
- 4、 Don't look at the LED light source for a long time. The high intensity light source may cause eye injury
- 5、 When you find the following problems, please seek the repair service to qualified electricians. Please don't disassemble them at will
 - 1) Products produce abnormal gas, abnormal sounds or unusual flashes;
 - 2) The shell is broken and the foreign body is invaded inside.

Note:

A:The above parameters can be modified without notification, if there is any change, according to the real object please.

B:We reserve the right to amend the data without any prior notification. sorry for the inconvenience caused.