Tapered Metal Tube Plugs JRRT9 & JRRT26





Application

For permanent sealing/plugging of leaky tubes in condensers and heat exchangers. Can be used to plug tubes or tube sheets.

Available sizes

Plug is available in sizes ranging from 1/4" OD to 1-1/2" OD. All gauges (BWG) are available. Larger plugs can be made as requested.

Tube Plug Type

Robinson offers two types of tapered metal tube plugs. Our JRRT9 style is a shorter drive in plug with al OAL of 1.860". Our JRRT26 style plugs is slightly longer with an OAL of 2.750".

Specifications

- A solid metal plug with taper, which allows one plug to fit a variety of different gauge tubes.
- One piece tapered tube plugs available in Aluminum, Chrome Moly, Monel, Titanium, Brass, Naval Brass, Stainless Steel 304,316,317,416, Duplex, Alloy 20, Carbon Steel, SA105, Cupro Nickel (70/30 & 90/10), Hastelloy, Incoloy.
 - Tapered tube plugs are also offered in other materials other than metals, such as: Buna, Fiber, Neoprene, Silicone, and Phenolic.
- Special Materials and custom sizing made to your specifications upon request.
- One piece plugs allow for easy and safe installation. Plugs are hammered in and have the option of being welded in place.

Storage Instructions

Keep plugs out of direct sunlight and store in a cool, dry area. Plugs have a long and indeterminable shelf life.

How to Install

- 1. For the best seal insert plugs into clean, dry tubes.
- 2. Place small end of plug into tube (or tube sheet).
- 3. Drive plug into tube with light hammer blows. Option of welding plugs into place.

Additional Tools

Hammer

When Ordering

Have the outside diameter (OD) and gauge (BWG) or inside diameter (ID) of your tubes, tube material, and quantity of tube plugs needed. Tube plug and tube material should always match. *One leaking tube needs two plugs; one for each end.

O.D.	GAUGE	JRRT9			JRRT26		
		BRASS	STAINLESS STEEL	STEEL	BRASS	STAINLESS STEEL	STEEL
1/4" 3/8"	15 - 22 11 - 14	JRRT9B250	JRRT9SS250	JRRT9S250	JRRT26B250	JRRT26SS250	JRRT26S250
3/8" 1/2"	15 - 22 11 - 14	JRRT9B375	JRRT9SS375	JRRT9S375	JRRT26B375	JRRT26SS375	JRRT26S375
1/2" 5/8"	15 - 22 11 - 14	JRRT9B500	JRRT9SS500	JRRT9S500	JRRT26B500	JRRT26SS500	JRRT26S500
5/8" 3/4"	15 - 22 11 - 14	JRRT9B625	JRRT9SS625	JRRT9S625	JRRT26B625	JRRT26SS625	JRRT26S625
3/4" 7/8"	15 - 22 11 - 14	JRRT9B750	JRRT9SS750	JRRT9S750	JRRT26B750	JRRT26SS750	JRRT26S750
7/8" 1"	15 - 22 11 - 14	JRRT9B875	JRRT9SS875	JRRT9S875	JRRT26B875	JRRT26SS875	JRRT26S875
1" 1-1/8"	15 - 22 11 - 14	JRRT9B1000	JRRT9SS1000	JRRT9S1000	JRRT26B1000	JRRT26SS1000	JRRT26S1000
1-1/8" 1-1/4"	15 - 22 11 - 14	JRRT9B1125	JRRT9SS1125	JRRT9S1125	JRRT26B1125	JRRT26SS1125	JRRT26S1125
1-1/4" 1-3/8"	15 - 22 11 - 14	JRRT9B1250	JRRT9SS1250	JRRT9S1250	JRRT26B1250	JRRT26SS1250	JRRT26S1250
1-3/8" 1-1/2"	15 - 22 11 - 14	JRRT9B1375	JRRT9SS1375	JRRT9S1375	JRRT26B1375	JRRT26SS1375	JRRT26S1375
1-1/2"	15 - 22	JRRT9B1500	JRRT9SS1500	JRRT9S1500	JRRT26B1500	JRRT26SS1500	JRRT26S1500

(JRRT9 - 1.860" Long) (JRRT26 - 2.750" Long)

Material Codes:

В ΤI Titanium Н Brass Hastelloy Stainless Steel SS Naval Brass C464 Duplex NB DP Steel S Chrome Moly CM Aluminum Α Cupro Nickel CUNI Phenolic PΗ