



Each Quick Drain Filter is reconfigurable. You can select from between 4 and 6 sides and up to 10 levels. The Quick Drain Filter shown here has 4 sides.

The inlet area is 14.53in^2 per section. For example, a 4 sided Quick Drain Filter with 5 levels (like the one shown here) has a total inlet area of $(14.53)*(4)*(5) = 29.60\text{in}^2$.

Each level has an inlet area of $(14.53)*(4) = 58.12\text{in}^2$.

Assemble with a threaded rod (sold separately) at each corner. We recommend using 3/8-16 threaded rods.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AGSOLUTIONS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AGSOLUTIONS IS PROHIBITED.				DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION
						Drawing by AgSolutions		
DRAWN	NAME	SIGNATURE	DATE			TITLE: Quick Drain Filter 4 Sided Configuration		
CHK'D								
APPV'D								
MFG								
Q.A				MATERIAL:		DWG NO.		A3
				WEIGHT: lbs		SCALE:1:10		SHEET 1 OF 1