



Each Quick Drain Filter is reconfigurable. You can select from between 4 and 6 sides and up to 10 levels. The Quick Drain Filter shown here has 6 sides.

The inlet area is 14.53in² per section. For example, a 6 sided Quick Drain Filter with 4 levels (like the one shown here) has a total inlet area of $(14.53) * (6) * (4) = 348.72 \text{ in}^2$.

Each level has an inlet area of $(14.53) * (6) = 87.18 \text{ in}^2$.

Assemble with a threaded rod (sold separately) at each corner. We recommend using 3/8-16 threaded rods.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AGSOLUTIONS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AGSOLUTIONS IS PROHIBITED.				DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION
						Drawing by AgSolutions		
DRAWN				NAME		SIGNATURE		DATE
CHK'D				NAME		SIGNATURE		DATE
APPV'D				NAME		SIGNATURE		DATE
MFG				NAME		SIGNATURE		DATE
Q.A				NAME		SIGNATURE		DATE
				MATERIAL:		DWG NO.		A3
				WEIGHT: lbs		SCALE:1:10		SHEET 1 OF 1