

# Slab Console™ Specs\*

MSRP \$6,995 USD

Designed and Built in the USA.



## Construction

### Console

CNC precision-milled, multi-layer MDF and furniture-grade plywood core for audio stability and supported by an aluminum frame. Every piece is hand-assembled and then finished with real wood veneer.

### Grill

Waterjet-cut aluminum backed by acoustically-transparent fabric. Grill attaches to console via magnets.

## Audio System

### 3 x Focal® 2-Way Coaxial 6.5" Speakers (Left, Center, Right Channels)

Power Handling (RMS): 80W  
Power Handling (Max): 160W  
Sensitivity (2.83V/1m): 93dB  
Impedance: 4Ω  
Frequency Response: 60Hz – 22kHz  
Cone: Kevlar Sandwich

### Reference 12" Subwoofer Speaker

Power Handling (RMS): 400W  
Power Handling (Max): 800W  
Sensitivity (2.83V/1m): 90.3 dB  
Impedance: 4Ω  
Frequency Response: 23Hz – 1kHz

### Subwoofer Amplifier

Power Output at 4Ω (RMS): 500W  
Total Harmonic Distortion: <1% THD+N  
Class D Mono Amplifier  
Auto On/Off  
Variable Level Control  
Variable Crossover Frequency  
Phase Controls

### Console Audio Inputs

#### Left, Center, Right Speaker Terminals (Passive)

Gold-Plated 5-Way Binding Posts  
3/4" Center-to-Center Spacing Allows for Dual Banana Plugs  
Accepts Up to 8 Gauge Wire

#### Dual RCA-type Subwoofer Input (Active)

Accepts the Output of an A/V Receiver's LFE Output  
Dual RCA Jacks Facilitate Line Level Loop-Through

## Dimensions

### Console Size

Height: 24"  
Width: 80"  
Depth: 21"

### Console Weight

390 lbs

### Under-Speaker Shelf

Height: 9" (Clears Subwoofer)  
Width: 74"  
Depth: 21"

## Electrical System

### Surge Protection and Line Filtering

AC 115V/230V Switchable  
IEC Power Socket  
6 AC Output Receptacles  
3000 joules AC surge suppression with EMI/RFI filtering  
Diagnostic LED  
15 Amp Capacity with Circuit Breaker

## System and Environmental Requirements

Separate A/V Receiver or Preamp/Amplifier Combo Required\*\*

Speaker System Rated for a 4Ω Load  
Power Handling per Channel (RMS): 80W  
Power Handling per Channel (Max): 160W

Operating Ambient Temperature: 32° to 95° F (0° to 35° C)

## In The Box

Slab Console  
Magnetic Speaker Grill  
Leveling Feet  
IEC Power Cable  
User Manual

\* Specifications are subject to change without notice. Please refer to the latest specification documents for up-to-date information.

\*\* Do NOT connect a receiver or amplifier with a higher power rating than the Slab Console's power handling rating. Doing so risks permanently damaging the Console's audio system.

