

CWS 500N1

CONTINUOUS WAVE SIMULATOR, 80W



FOR TESTS ACCORDING TO ...

- > BMW GS 95002 (2001)
- > DaimlerChrysler DC-10614
- > DaimlerChrysler DC-11224
- > EN 300329
- > EN 300340
- > EN 300342-1
- > EN 300386 V1.3.2
- > EN 301489-1
- > EN 301489-17
- > EN 301489-24
- > EN 301489-7
- > EN 55024
- > EN 61000-6-1
- > EN 61000-6-2
- > Fiat 9.90110
- > Ford ES-XW7T-1A278-AB
- > Ford ES-XW7T-1A278-AC
- > GMW 3097 (2006)
- > IEC 60601-1-2
- > IEC 61000-4-6
- > IEC 61326
- > IEC 61850-3
- > ISO 11452-4
- > Mercedes MBN 10284-2
- > ...






CWS 500N1 - THE SINGLE BOX SOLUTION FOR RF CONDUCTED IMMUNITY TESTING

The CWS 500N1 is the most compact single box test equipment for testing conducted rf immunity as per IEC 61000-4-6 and related standards. Apart from the 1kHz 80% AM signal the CWS 500N1 also generates a 2 Hz 80% AM signal to test medical appliances and a 1 Hz PM signal with 50% duty cycle required to test safety equipment like fire alarms. Equipped with a 1 GHz current monitor the CWS 500N1 can be used up to 1 GHz by means of an external amplifier. EM TEST supplies a large range of CDNs, EM clamp and current injection clamps as well as the corresponding calibration accessories. Full compliant levelling can be run from the front panel of the CWS 500N1 storing the results in one of the 5 memories.

HIGHLIGHTS

- > **SIGNALGENERATOR 9KHZ TO 1GHZ**
- > **AMPLITUDE MODULATION: 1HZ TO 3KHZ (0% TO 95%)**
- > **PULSE MODULATION: 1HZ - 1KHZ (10% TO 90%)**
- > **USB-INTERFACE**
- > **AUTOMATIC CALIBRATION VIA BUILT-IN POWER METER**

APPLICATION AREAS

-  INDUSTRY
-  RESIDENTIAL
-  MEDICAL
-  BROADCAST
-  TELECOM

TECHNICAL DETAILS

TEST LEVEL

Output level	1V - max. 30V (emf) all standard test levels are guaranteed with all coupling methods
Output power	80W (nominal)
Output impedance	50ohm
Harmonic distortion	Less than -20dBc at 20W

TEST FREQUENCIES

Sinus (CW)	100kHz to 300MHz
Frequency bands	100kHz to 9.999MHz 10MHz to 99.99MHz 100MHz to 300MHz in the Quick Start menu the step size can be selected by the operator
Unmodulated signal	CW (continuous wave)
Amplitude modulation	1kHz, 80%AM as per IEC 61000-4-6 2Hz, 80%AM as per IEC 60601-1-2 400Hz, 80%AM
Pulse modulation	1Hz, 50% duty cycle as per EN 50130-4

MEASUREMENTS

Monitor	Integrated RF power meter, measuring input for CDN and clamp calibration as well as current monitor for clamp applications
RF indicator	LED indicating the RF output status
LCD	Online display of the test level and the preselected frequency value
Cal data F1 - F5	5 internal memories to save calibration data, 1% step width as required by the standard

TIME PARAMENTERS

Dwell time for CW & AM	td = 0.3s to 9,999s
Dwell time for PM	td = 3s to 9,999s
Pause time	tr = 0/0.3s to 9,999s

OUTPUT

Direct RF output	BNC (on the front panel)
------------------	--------------------------

TEST ROUTINES

Quick Start	Immediate test start; easy-to-use and fast
User Test routines	Voltage sweep Frequency sweep Dwell time sweep
Standard Test routines	Level 1 to Level 3 (IEC 61000-4-6) Automatic Level X to Level Y
Cal procedure	Calibration of the complete test set-up, calibration data saved in internal memory
Service	Service, set-up

SIGNAL GENERATOR

Output level	-55dBm to 0dBm
Frequency range	9kHz to 1GHz
Output impedance	50ohm
Direct RF output	To control an external amplifier

MEASUREMENTS FOR BCI APPLICATION

PM 1000	3-channel power meter up to 1GHz - to measure the Forward power - to measure the Reverse power - to measure the injected current
---------	---

INTERFACE

Serial interface	USB
Parallel interface	IEEE 488, addresses 1 to 30
Fail 1	BNC input; test will be stopped when active low
Fail 2	BNC input; test status will be saved (max. 10 events) when active low. Test will continue.

GENERAL DATA

Dimensions, weight	19"/3HU, approx. 17kg
Supply voltage	115V to 230V +10/-15%, 50/60Hz
Input power	Max. 380W
Power factor	cos (phi) = 0.98 at max. output power as per IEC 555
Fuses	2 x 6.3AT (115V) or 2 x 3.15AT (230V)
Cooling	Active cooling, air ventilation
Temperature	10°C to 40°C
Rel. humidity	Max. 85%, non condensing

TECHNICAL DETAILS

OPTIONS	
ATT6/75	6dB attenuator, 75W
ATT20/0.5	20db attenuator, 0.5W for the calibration of CDNs and clamps (included with the PM 1000)
CDNs	As per IEC 61000-4-6 (refer to separate list)
Clamps	EM clamp as per IEC 61000-4-6 Current injection clamps Current monitoring clamps
T-50	50ohm termination resistor for CDNs and clamps
R-100x	150ohm-to-50ohm matching impedance for calibration
Cal adapters	For all types of CDNs and clamps
icd.control	Extensive and most versatile remote control and reporting software. A standard library helps to configure the test setup. Multiple interruption functions automated by IEEE instruments or manually. Easy to use or expandable to complex test routines on the base of vector definitions.

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST AG > Sternenhofstraße 15 > 4153 Reinach > Switzerland
Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199
Internet: www.emtest.ch > E-mail: sales@emtest.ch

Germany

EM TEST GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland
Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050
Internet: www.emtest.com > E-mail: info@emtest.de

France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France
Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55
Internet: www.emtest.fr > E-mail: info@emtest.fr

Poland

EM TEST Polska > ul. Lema 33, 26-613 Radom > Polska
Phone +48 518 64 35 12 > E-mail: info.polska@emtest.de

USA / Canada

EM TEST USA Inc. > 3 Northern Blvd. Unit A-4 > Amherst > NH 03031
Phone +1 (603) 769 3477 > Fax +1 (603) 769 3499
Internet: www.emtest.com > E-mail: sales@emtest.com

P.R. China

EM TEST Representative Office Beijing > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
Internet: www.emtest.com > E-mail: emtestbj@public.bta.net.cn

Malaysia

EM TEST (M) SDN BHD > Unit B2-6, Jalan Dataran SD2 > Dataran SD2, PJU9 > Bandar Sri Damansara > 52200 Kuala Lumpur > Malaysia
Phone +60 (03)62 73 22 01 > Fax +60 (03)62 74 22 01
Internet: www.emtest.com > E-mail: sales@emtest.com.my

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release.
Technical data subject to change without further notice.