



# IPB4

Capacitive Coupling Clamp  
for EFT / Burst according to  
IEC/EN 61000-4-4 Edition 3

*Datasheet*



**HAEFELY**

Current and voltage – our passion

Designed by



# General Description

The IP4B capacitive coupling clamp is primarily used to inject fast transient and burst interference pulses into signal and data cables, i.e. into any type of connection to peripheral equipment. The IEC standard 61000-4-4 Ed. 3 also allows the capacitive coupling method to be used for pulse injection into AC and DC power lines when no appropriate decoupling network is available.

The coupling capacitance (typically 100pF) between the coupling clamp and the cable inserted depends on the cable type, the diameter and other factors like screening, etc.

## Features

- Designed as per IEC 61000-4-4 Edition 3
- EFT/Burst testing of signal and data lines
- For cable diameter from 4 – 40 mm
- Active coupling length 1 m

## Applications

- Capacitive Coupling according to IEC/EN 61000-4-4 Ed. 3

## Scope of Supply

- Coupling clamp IPB4
- Connecting cable Fischer/SHV
- Calibration certificate

## Technical Data

### Applicable Standards

General	IEC/EN 61000-4-4 Ed.3
---------	-----------------------

## Global Presence

### Europe

HAEFELY AG  
Birsstrasse 300  
4052 Basel  
Switzerland

☎ + 41 61 373 4111  
✉ [sales@haefely.com](mailto:sales@haefely.com)

### China

HAEFELY AG Representative Office  
8-1-602, Fortune Street, No. 67  
Chaoyang Road, Beijing 100025  
China

☎ + 86 10 8578 8099  
✉ [sales@haefely.com.cn](mailto:sales@haefely.com.cn)

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up to date.  
©Copyright HAEFELY/ Subject to change without notice

V20XX.XX



**HAEFELY**

Current and voltage – our passion



HIGH VOLTAGE



INSTRUMENTS



EMC

  
precision.  
**swiss made.**