

VSS 500N6.4

VOLTAGE SURGE GENERATOR



FOR TESTS ACCORDING TO ...

- › ANSI/IEEE C37.90
- › EN 60255-27
- › EN 60255-5
- › IEC 60255-27
- › IEC 60255-5
- › IEC 60747-5
- › IEC 61180-1
- › IEC 62052-11

VOLTAGE SURGE SIMULATION

The surge simulator type VSS 500N6 generates high voltage transients as required by IEC 60255-27 with a source impedance of 500ohm for transient overvoltage tests on "Protection Relays". The output voltage ranges up to 6.6kV, covering for tests levels 1 to 5.

The no-load waveshape corresponds to IEC-61180-1. For this kind of testing the IEC 60255-27 standard requires a fixed energy of 0.5 J at the 1000 V and 5000 V test levels.

HIGHLIGHTS

- › Surge pulse 1.2/50 us up to 6.6 kV
- › 5 different test levels, (1 & 5 kV; IEC 60255-27)
- › Source impedance 500ohm
- › Constant Energy of 0.5J at each test level
- › Peak voltage/current measurement
- › Spark-over detection
- › Interlock
- › Warning lamp control

APPLICATION AREAS

-  COMPONENTS
-  INDUSTRY
-  RESIDENTIAL

TECHNICAL DETAILS

MODEL OVERVIEW

MODELS VSS 500N6

VSS 500N6.4	0.55kV, 1.0kV, 3.0kV, 5.0kV, 6.6kV
-------------	------------------------------------

TECHNICAL DETAILS

VOLTAGE SURGE SIMULATOR, PULSE 1.2/50 US

Voltage (o.c.)	250 V - 6,600 V ±10 %
----------------	-----------------------

Pulse front time	1.2 us ± 30 %
------------------	---------------

Pulse time to half value	50 us ± 20 %
--------------------------	--------------

Source impedance	500 Ohm
------------------	---------

Energy	0.5 J ± 0.05 J at each test level
--------	-----------------------------------

Pulse forming	As per IEC 60255-27 (previous -5)
---------------	-----------------------------------

Polarity	Positive, negative or alternating
----------	-----------------------------------

Event counter	1 - 30,000 or endless
---------------	-----------------------

TRIGGER

Trigger of events	Automatic, manual, external
-------------------	-----------------------------

CRO trigger	5V trigger signal for oscilloscope
-------------	------------------------------------

Synchronization	0° - 360°, resolution 1°
-----------------	--------------------------

Repetition rate	6 s - 999 s, depending on the voltage
-----------------	---------------------------------------

TEST LEVELS

VSS 500N6.4	0.55kV, 1.0kV, 3.0kV, 5.0kV, 6.6kV
-------------	------------------------------------

OUTPUT

Direct	Via HV connector; Zi = 500 Ohm To connect external test boxes or devices
--------	---

MEASUREMENTS

Peak voltage	6,600 V in the LCD display
--------------	----------------------------

Peak current	13 A in the LCD display
--------------	-------------------------

TECHNICAL DETAILS

TEST ROUTINES

Quick Start	Immediate start; easy-to-use and fast
-------------	---------------------------------------

User Test routines	Change Polarity after n pulses Change voltage after n pulses Change phase angle after n pulses
--------------------	--

Standard Test routines	As per IEC 60255-27, Level 1 - 5
------------------------	----------------------------------

Service	Service, set-up, self test
---------	----------------------------

INTERFACE

Serial interface	USB
------------------	-----

Parallel interface	IEEE 488, addresses 1 - 30
--------------------	----------------------------

SAFETY

Safety circuit	Control input (24 Vdc)
----------------	------------------------

Warning lamp	Floating output contact
--------------	-------------------------

GENERAL DATA

Dimensions, weight	19"/3HU, 16.1 kg
--------------------	---------------------

Supply voltage	115/230 V +10/-15 %
----------------	---------------------

Fuses	2 x 2 AT (230V) or 2 x 4 AT (115V)
-------	------------------------------------

ENVIRONMENT

Temperature	10 °C to 35 °C
-------------	----------------

Humidity	30 % to 75 %, non condensing
----------	------------------------------

Atmospheric pressure	86 kPa (860 mbar) to 106 kPa (1,060 mbar)
----------------------	---

OPTIONS

OPTIONS

HV Contacts	Pair of gun-type HV contacts for safe application of the HV pulses to the EUT
-------------	---

iec.control	Remote control and documentation software, including standard test routines and reporting capabilities.
-------------	---

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

AMETEK CTS GmbH › Sternenhofstraße 15 › 4153 Reinach › Switzerland
Phone +41 (0)61 204 41 11 › Fax +41 (0)61 204 41 00
Internet: www.ametek-cts.com › E-mail: sales.conducted.cts@ametek.com

Germany

AMETEK CTS Europe GmbH › Customer Care Center EMEA › Lünener Straße 211
› 59174 Kamen › Germany
Phone +49 (0) 2307 26070-0 › Fax +49 (0) 2307 17050
Internet: www.ametek-cts.com › E-mail: info.cts.de@ametek.com

Poland

AMETEK CTS Europe GmbH › Biuro w Polsce › ul. Twarda 44 › 00-831 Warsaw › Poland
Phone +48 (0) 518 643 12
Internet: www.ametek-cts.com › E-mail: Infopolska.cts@ametek.com

USA / Canada

AMETEK CTS US › 52 Mayfield Ave › Edison › NJ 08837 › USA
Phone +1 732 417 0501
Internet: www.ametek-cts.com › E-mail: usasales.cts@ametek.com

P.R. China

AMETEK Commercial Enterprise (Shanghai) Co. Ltd. › Beijing Branch › Western Section, 2nd floor › Jing Dong Fang Building (B10) › Chaoyang District › Beijing, China, 100015
Phone +86 10 8526 2111 › Fax +86 (0)10 82 67 62 38
Internet: www.ametek-cts.com › E-mail: chinasales@ametek.com

Republic of Korea

EM TEST Korea Limited › #405 › WooYeon Plaza › #986-8 › YoungDeok-dong › Giheung-gu › Yongin-si › Gyeonggi-do › Korea
Phone +82 (31) 216 8616 › Fax +82 (31) 216 8616
Internet: www.emtest.co.kr › E-mail: sales@emtest.co.kr

Singapore

AMETEK Singapore Pte. Ltd › No. 43 Changi South Avenue 2 › 04-01 Singapore 48164
Internet: www.ametek-cts.com › E-mail: singaporesales.cts@ametek.com

Great Britain

AMETEK GB › 5 Ashville Way › Molly Millars Lane › Wokingham › Berkshire RG41 2 PL › Great Britain
Phone +44 845 074 0660
Internet: www.ametek-cts.com

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.