



## 877-TUB-CAST

## Ekopel 2K Surround Kit

### Application Instructions

GLOVES ARE RECOMMENDED

#### Tips:

*Warm the bathroom to 75 degrees fahrenheit or higher for a minimum of 12 hours prior to application. This can be best accomplished by placing a portable heater inside the bathtub and leaving the bathroom door closed.*

*Fill large chips if necessary with a high-quality auto body filler after the tub is fully cleaned.*

#### Mixing/Pouring

1. Begin mixing Ekopel 2K **(10 minutes hand mix, 5-10 minutes rest- 1-2 minutes stir.)**
2. Once you finish the first kit begin mixing 2nd kit and follow remaining mixing instructions.
3. From the top of the unit pour full contents of container around the walls.
4. Use included roller to push and move coating until all walls are covered. **(This coating is thick and will need to be moved several times.)**
5. Lightly roll to side all walls to even out coating **(Self leveling will take over from there.)**
6. Scoop excess rundown into the can or push up the tub walls with foam roller. **(Video example is helpful here.)**
7. Using foam roller push excess material from the top rail of tub applying light pressure. Moving material in pooling areas over any missing stops on walls.
8. Pour all scooped material onto top front rail, run roller with pressure to push material to Flow on inside and outside tub walls. Scoop extra and rapport if needed.
9. Move material up tub inside wall. Roll outside tub skirt and any further missed areas.
10. Level out and remove excess from bottom of tub. Remove tape from walls.
11. Use Heat Gun or Hair Dryer to pop micro foam bubbles. This prevents staining while it oxidises. Then remove tape.
12. After 1 hour remove the tape dam. Hourly scoop off/wipe excess material off drain/floor tape.
13. Wait until aterial stops moving into drain area, remove remaining tape **(After 4-6 hours.)**
14. Remove any wet Ekopel with alcohol or acetone if needed.
15. Remove tape, wait 24-36 hours for use.

**Follow Our Full Demo**

YouTube: [Refinished Bath Solutions](#)

Also on our website: [refinishedbathsolutions.com](http://refinishedbathsolutions.com)

EMERGENCY AND FIRST AID - IF THIS PRODUCT COMES IN CONTACT WITH EYES, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES AND CONSULT PHYSICIAN IF IRRITATION PRESISTS. IN CASES OF SKIN CONTACT, WASH WITH SOAP AND LARGE QUANTITIES OF WATER AND REMOVE SAT - URATED CLOTHING. IF BREATHING DIFFICULTIES, DIZZINESS OR LIGHTEADEDNESS OCCUR WHEN WORKINGIN AREAS WITH HIGH VAPOR CONCENTRATIONS. VICTOM SHOULD BE REMOVED TO AIR THAT IS FREE FROM VAPORS. IF VICTOM CONTINUES TO EXPERIENCE BREATHING DIFFICULTIES OXY-GEN SHOULD BE ADMINISTERED UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. IF BREATHING STOPS BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. IF THIS PRODUCT IS SWALLOWED. DO NOT INDUCE VOMITING SEEK IMMEDIATE MEDICAL ATTENTION.