

GRASS GOAT INSTALLATION INSTRUCTIONS

Includes: 1 Metal Cutting Blade, 1 Blade Adapter Plate, 1 Trolling Motor Shaft Support Bracket, 1 Large Hose Clamp, 1 Small Hose Clamp, 2 Small Screws

- 1. Attach the Trolling Motor Shaft Support Bracket to the top of the Blade Adapter Plate.**
- 2. Push the Support Bracket firmly against the trolling motor shaft.**
- 3. Use the small hose clamp to make sure the adapter plate holds tight to the shaft of the trolling motor for horizontal support.**
- 4. Use the large hose clamp to go around the bottom of the motor and tighten for vertical support.**
- 5. Starting with the bottom of the blade, spin the trolling motor prop and make sure the bottom of the prop doesn't touch the Grass Goat Blade. The gap should be around 1/16", then tighten the bottom screw.**
- 6. Spin the prop until one of the ears on the trolling motor prop is straight up. Push the prop towards the Grass Goat Blade to make sure there is enough room for the blade to flex and make sure that it will not hit the blade while it is spinning. Tighten the top screw.**
- 7. Spin the prop to make sure the prop clears the blade during rotation.**

The gap between the Grass Goat blade and the top of the trolling motor prop will be greater than the gap at the bottom because as the trolling motor is in motion, the top of the prop flexes with speed.