

# Gfp 800 Series

## Professional Dual Heat Laminators

Our most flexible, cost-effective laminator yet.



For finishing professionals who need versatility, quality, and economy in one machine, the **Gfp 800 Series** delivers. Turn out thermal encapsulation with low melt films (1.5-10mil), PSA lamination, and mounting jobs quickly and easily. Operators will spend less time on set-ups and changeovers thanks to swing out supply shafts and film rolls up to 10" in diameter. Two front rewind shafts allow thermal encapsulation of prints from a roll.

Versatile productivity for the bottom line – That's the **Gfp** difference.

- ✓ Two swing out supply shafts
- ✓ Two front unwind shafts
- ✓ Roller diameter 5.25"
- ✓ Web clutch adjustment
- ✓ Variable roller gap 1"
- ✓ Motorized rear rewind option
- ✓ Infinitely variable nip adjustment
- ✓ Independent top/bottom heaters
- ✓ Swing up feed table
- ✓ Dual tension controls
- ✓ Print pressure plate
- ✓ 36" table height output
- ✓ Silicone rollers
- ✓ CE Certified



**Remington**  
*laminations*  
**Incorporated**

*The Ultimate Bond and Protection!*

Contact us @ 817-488-8700

# Choose a Gfp Professional Dual Heat Laminator for *Mounting Laminating Encapsulating*



Two front unwind shafts for roll-to-roll encapsulation.

Motorized rear  
rewind for roll-to-roll  
applications



Front and rear  
Swing-out Film  
Shafts

## Applications

Signs  
Banners  
Trade show displays  
Point-of-purchase  
Dry-erase boards  
Floor graphics  
Graphic mounting  
Photo mounting  
Window graphics  
Vehicle graphics

## Specifications

	847DH	865DH
Laminating Width	47"	65"
Roller diameter	5.25"	5.25"
Roller gap	1"	1"
Supply roll diameter	Max 10" OD	Max 10" OD
Rear rewind	Optional	Optional
Max temperature	266° F	266° F
Film thickness	1.5 - 10 mil	1.5 - 10 mil
Laminating speed	0-13 ft/min	0-13 ft/min
Drive motor	DC geared motor	DC geared motor
Pressure adjustment	Dual hand wheels	Dual hand wheels
Roller heating	Dual (Top/Bottom)	Dual (Top/Bottom)
Power supply	220v 60Hz Single phase/22 amps	220v 60Hz Single phase/22 amps
Power consumption	Max 4400W	Max 5700W
Net weight with stand	601 lbs.	767 lbs
Dimensions	69" x 34" x 49"	87" x 34" x 49"
Installation	Included	Included
Warranty	1 year parts and labor	1 year parts and labor



**Remington  
laminations  
Incorporated**

*The Ultimate Bond and Protection!*

Contact us @ 817-488-8700