



SEAL® 54 EL Laminator



The SEAL 54 EL is a high quality, affordably priced cold roll laminator specifically designed for new users to confidently create professionally-finished wide format graphics. Built for safety and ease of use, this sturdy machine is just right for laminating and mounting pressure-sensitive graphics up to 54" wide. Its durable uniframe construction requires no assembly and minimal maintenance. Made in the U.S.A. and backed by the most dependable manufacturer in the industry, the 54 EL is a smart option for entrance into the wide format graphics market.

The SEAL 54 EL provides the following features:

Optimum performance

- High quality, professional finishing results
- Manually adjustable nip to 1" for easy handling of most any substrate
- Durable uniframe construction
- Fast 14ft/min production speed
- Best warranty in the industry

Ease of use

- Auto-grip shafts
- Roll feed capable
- Additional supply shaft storage available
- Simple controls
- Minimal maintenance
- Flip up in-feed table for easy webbing

Safety

- ETL listed for US/Canada
- CE approved
- Foot switch for hands free operation
- Safety eyes for increased operator safety

Incorporating technology and intelligence from the SEAL family of machines, the 54 EL combines a sturdy industrial level design with uncomplicated operation at an entry-level price point. It includes simple controls, a flip up in-feed table for easy webbing, new light weight auto-grip shafts and a manually adjustable nip to 1" for easy handling of most substrates.

As with all SEAL laminators, the 54 EL is manufactured in the U.S.A. at our ISO Certified facility and offers the best warranty in the industry. With its CE and ETL certifications, owners can have peace of mind in the safety and reliability of the this machine. The 54 EL is a smart choice for entrance into the wide format graphics market.

The SEAL 54 EL is ideal for a wide variety of display applications.

Creating Decals



Applying Pre-mask



Mounting to Rigid Substrates



Single Sided Lamination




Technical Specifications

	English	Metric
Max. Working Width	54" maximum	1372 mm max
Max. Speed	14 ft/min	4.25 m/min
Dimensions (HxWxD)	48" x 22.1/2" x 75.1/4"	1219 x 1911 x 572mm
Shipping dimensions (HxWxD)	54" x 74 3/4" x 25"	1372 x 1899 x 635mm
Weight		
Net Weight	325 lbs	147 kg
Shipping Weight	440 lbs	200 kg
Maximum roll diameter		
Unwind	8"	200 mm
Take-up	6"	150mm
Maximum roll weight		
Unwind	85 lbs	38.5 kg
Take-up	35 lbs	15.9 kg
Roller Opening (Min. – Max.)	0 – 1"	0 – 25mm
Roller Pressure	3 lbf/in	0.53 N/mm
Electrical Specifications		
US/Canada	115 VAC, 50/60Hz, 1A, 115W - NEMA 5-15 Plug	
Europe	230 VAC, 50/60Hz, 0.5A, 115W - BS1363 Plug or Continental Europe Plug (Schuko style)	
Roller Construction	Two silicone covered steel rollers	
SEAL 54 EL Part Number	54545	
Optional Equipment Part Numbers		
Roll Trough - Factory/Field Installed	5401/5402	
Autogrip Shaft Storage Kit - Factory/Field Installed	5403/5404	

* Specifications may change without notice.



Ergonomic control panel for ease of use.



Manual nip adjustment with height gauge for precise operation.



Heavy duty rear stabilizing feet.



Light-weight auto grip shafts for user friendly webbing.

Neschen Americas
7091 Troy Hill Drive
Elkridge, MD 21075
U.S.A.

Tel: 800-257-7325
Local: 410-540-8900
Fax: 800-966-4554

Neschen Americas Canada
1601 Matheson Blvd E., Unit 4
Mississauga, Ontario
Canada L4W 1H9



Contact your local distributor:

Remington Laminations, Inc
2022 W.NW HWY, SUITE 108
GRAPEVINE, TX 76051
TEL. 877-317-1716 FAX. 817-488-8700
WWW.REMINGTONLAMINATIONS.COM