

MEASUREMENTS

HEIGHT	183 cm.
WIDTH	72 cm.
DEPTH	84,5 cm.
WEIGHT	190 kilos.


STANDARD VERSION

Internal temperature of 8°C


3°C VERSION


TRAYS	From 5 to 7 - standard version 6.
SPIRALS	In steel 13 different models, see layout; bars and plinths for dispensing cans and bottles. SPIRAL REVOLUTION SYSTEM.
MATERIAL	Metal.
ILLUMINATION	LED.
DISPLAY	Graphic; one can use all graphic fonts, graphic icons and program 8 different spots. The display shows the commands contemporaneously in 2 different languages (of your choice). Programmable stand-by .
CHILLER UNIT	Compact chiller with rapid extraction. Ecological refrigerator gas R404A. Internal temperature of 8°C with external temperature at 32°C. 3°C version. Optional quieter chiller. Programmable stand-by.
OPTIONALS AND ACCESSORIES	Elevator system with programmable heights. Streetstyle (re-inforced door) with burglar resistant grill. Anti-vandalism coin insert. Locking cash box. Optical sensor for assured vending. Age control reader. Quieter chiller. 3°C version. SD card reader. Logic board programmer. Double Executive 110V version available.
TECHNOLOGY	EVA-DTS. GPE-DATA (usable with Excel type program). Software which can be updated by PC or by logic board programmer. Data logger with detailed information on every single vend. Programmable expiry date. Programmable stand-by with clock also weekly based for chiller, display case and display.
PAYMENT SYSTEMS	Executive protocol. MDB protocol. Direct parallel coin mechanism.
ELECTRICAL POWER SUPPLY	For each hour of stand-by, with ambient temp. 20°C with chiller at 5°C : 235 Wh; with chiller at 8°C :170 Wh.
ABSORBED POWER	540 W.
DESIGN	Italian style – by Architects Floris & Giommi.