

# HITCH TRAY CARGO BAG



Your Hitch Tray Cargo Bag is designed to mount to an existing hitch tray cargo carrier. Six lashing straps hold the Cargo Bag to the cargo carrier.

## INSTALLATION

1. Spread out the Cargo Bag onto your cargo carrier so that the bag opens away from the vehicle.
2. Unzip the Cargo Bag completely and load the bag by placing larger and heavier objects into the bag first. Continue to load the Cargo Bag by placing smaller and lighter items on top of the heavier and larger items.
3. Close the zipper completely.
4. Attach the long end of the lashing straps to the buckles on the top of the bag. **See figure 1**
5. Attach the short end of the lashing straps to the cargo carrier. **See figure 2**
6. Firmly tighten down the straps.

## NOTES:

- When traveling, periodically check the straps to ensure they have not loosened.
- Tuck excess webbing away and tie it off to avoid flapping while driving.
- Do not leave the empty Cargo Bag on the vehicle.
- Do not exceed the cargo carrier's rated load capacity.

## WARNING:

If the cargo carrier or the contents being transported are inline with the exhaust outlet, an exhaust tip must be used to redirect the exhaust flow away from the cargo platform or contents.




Fig 1




Fig 2

---

Save 5% on your next purchase at **Winterial.com**  
with the coupon code **WinterialFive** at checkout!