
Victory Girl Custom Contour-cut Vinyl INSTALLATION INSTRUCTIONS

Thank you for your Victory-Girl vinyl decal purchase. Each decal is covered in a transparent transfer tape, to allow for easy placement and installation of small or complex pieces onto a prepared surface.

Clean the surface where the decal is to be installed with a mild glass cleaner (4 parts water, one part glass cleaner) and wipe dry with soft towel.


(this material is a DRY installation; surface underneath the vinyl should be completely dry before placing vinyl on surface).

Cut the decal backing material at the top to allow the top of decal to touch the edge.** Do not cut the transfer tape; use it to hold the top of the decal in place while you position it.



top layer is

cut white backing



Ensure the decal is aligned properly from top to bottom (or side to side)..

Slowly peel away the backing material, rolling it away from the decal material, while carefully smoothing the decal material downwards with, steady, short strokes. Press out any bubbles towards the edges of the material., using a squeegee or other rigid, smooth-edged tool. You can gently pull the decal up and away from the surface using the transfer tape to reposition it

Victory Girl Custom Contour-cut Vinyl INSTALLATION INSTRUCTIONS

Once all the backing paper is removed, and the decal is sitting on the surface, begin to gently pull the transfer tape down and away from the decal, smoothing out bubbles that might appear in the decal material. Using a firm sponge or rubbing with soft towel will help avoid tears during this process.

If you need to place the decal over uneven areas (like rivets), you can use a hair dryer or heat gun set to'Low' to heat the vinyl (after you've removed the transfer tape), to shrink the vinyl to uneven surface areas during installation. Use caution, however, as too much heat will warp the vinyl. After it cools it will 'shrink' tight to the uneven surface.



The decal is easily removable up to 36 hours after installation. For removal of decal after this period, use of a heat gun to soften the vinyl/glue will ease removal without damage to paint.