

CANOE RACK

Model #11-3600



PARTS LIST	
Qty	Name
2	Canoe Rack with Pad & Safety Strap
4	Phillip Head Screw

Mounting to Wall*

Tools Needed: Tape Measure, Electric Drill, $\frac{3}{16}$ " Drill Bit, and a #3 Phillips Head Driver

The length of your Watercraft will determine arm spacing. Ideal arm spacing is 40% of total boat length, meaning your 10' boat x 0.4 = 4' arm spacing.

1. Locate studs where arms will be mounted and mark desired height for the arms. Push a mounting screw into wall to mark the locations for holes. Studs are typically on 16" centers. *Screwing only into drywall is not sufficient and could result in injury to self and Board.*



Pro Tip: An old woodworkers trick is to rub the screw threads on a bar of soap for easy installation.

2. Pre-drill pilot hole for Phillips Head screw using a $\frac{3}{16}$ " drill bit.
3. Use #3 Phillips Head Driver to drive the screws into the wall. Initially, leave top screw loose (helps when locating hole for lower screw). After inserting bottom screw, tighten both screws.
4. Mount second arm at same height as first arm.

*These Racks can also be attached to the SuspENZ Over-Water 2-Boat Dock Frame #32-0633 using bolts that are included with the frame hardware.

Rev. 10/20

FOR TECHNICAL ASSISTANCE OR REPLACEMENT PARTS: CALL 866.787.7369

OUR PLEDGE TO YOU

SuspENZ® products are warranted to the original owner against defects in material and workmanship when used for its intended purpose under normal use and conditions for one year. It is at the discretion of SuspENZ to repair or replace any defective product.

SUSPENZ, INC.
8725 ROSWELL ROAD #0-220
ATLANTA GA 30350



CUSTOMER SERVICE: 770-518-0045
FAX: 770-518-8507
WEBSITE: WWW.SUSPENZ.COM