

# BALLOON SAND WHEEL CONVERSION KIT

Model # 22-2219



PARTS LIST	
Qty	Name
2	Balloon Wheels
2	Axle Converter
2	Axle Locking Pin
2	Quick-Release Pin
1	Air Pump

Holds up to 200 LBS

## Assembly

1. Remove existing airless wheels from cart frame.
2. Slide *Axle Converter* over existing axle. Secure with *Axle Locking Pin* so that *Pin* hangs down.
3. Inflate *Balloon Wheels* with the included *Air Pump*. When inflated, wheel has a diameter of 12" to 13". It will feel soft, that is why it works well in sand.
4. Slide *Balloon Wheel* over converted axle then insert a *Quick-Release Pin* in hole next to wheel and flip the lock ring over the end of the axle to secure the wheel in place.
5. Repeat process for other side of the cart.

**Note:** If wheels are "plowing sand" instead of riding over the sand, inflate wheels an additional 3 to 5 pumps.

Rev. 11/18

FOR TECHNICAL ASSISTANCE OR REPLACEMENT PARTS: CALL 866.787.7369

## OUR PLEDGE TO YOU

Suspenz® products are warranted for life against defects in material or workmanship to the original owner. Product must be used for its intended purpose under normal conditions. Please visit [www.Suspenz.com](http://www.Suspenz.com) for complete warranty information.

SUSPENZ®, INC.  
8725 ROSWELL ROAD #0-220  
ATLANTA GA 30350



CUSTOMER SERVICE: 770-518-0045  
FAX: 770-518-8507  
WEBSITE: [WWW.SUSPENZ.COM](http://WWW.SUSPENZ.COM)