

Z-RACK SAFETY STRAPS

Model #
99-0006



Parts List	
2	Strap
2	Plastic Web Cap
2	Steel Web Bracket
2	Hex Bolt
4	Washer
2	Lock Nut



Step 1: Remove plastic end cap from the front side of the rack. Insert new **Plastic Web Cap** so the slot for the strap is facing outward.

Step 3: Open **Safety Strap** (release Velcro), thread strap through the Plastic Web Cap and the Steel Web Bracket then secure by pressing Velcro together.

Step 4: Repeat above steps for 2nd rack. Then place Kayak/SUP in rack.

Step 5: Place **Safety Straps** over Kayak/SUP; buckle straps together then pull for a snug fit.



Step 2: Attach **Steel Web Bracket** through holes in top/back of Rack securing with **Hex Bolt, 2 Washers** and **Lock Nut**.

Rev. 05/20

FOR TECHNICAL ASSISTANCE OR REPLACEMENT PARTS: CALL 866.787.7369

OUR PLEDGE TO YOU

SuspENZ® products are warranted to the original owner against defects in material and workmanship when used for its intended purpose under normal use and conditions for one year. It is at the discretion of SuspENZ to repair or replace any defective product.

SUSPENZ, INC.
8725 ROSWELL ROAD #0-220
ATLANTA GA 30350



CUSTOMER SERVICE: 770-518-0045
FAX: 770-518-8507
WEBSITE: WWW.SUSPENZ.COM