



The pump is a light and compact high head submersible clean water automatic pressure system pump supplied wired and ready to install. The pump includes an electronic automatic restart pump control with dry run protection.

The pump is characterised by:

- Corrosion resistant pump components.
- Fully automatic operation.
- Shaft seal with sand protection boot.
- 240V single phase motor with in-built auto reset thermal overload.
- 15m of power cable.
- 2 year warranty.
- Flows to 95 l/m
- Heads to 46 m

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	750W
Rated output:	1100W
Current:	4.8 amps
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	F
Power cable length:	15 m H07RNF
Net weight:	11.0 kg
Dimensions:	480L x 150H x 150W (mm)

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

Pump body:	Noryl
Impellers (4):	Noryl with stainless steel wear ring
Diffusers (4):	Noryl with floating dry run resistant wear ring
Pump shaft:	SS416
Shaft seal:	Nitrile

Installation:

Maximum ambient temperature:	40 °C
Maximum submergence:	15m.
Pipe connections discharge:	1"

2 Year Dab Pump Warranty

