



DA Irrigation Sprinklers

The Standard Irrigation Sprinkler (Dual Arm "DA") has been in use for 58 years, in and adjacent to the Sydney Metropolitan Area. They have a wide variety of uses from **Agricultural Crop Irrigation, Nursery Irrigation, Poultry, Shed Cooling, Crop Spraying & Fertilizing** and [Bushfire Alleviation](#).

Important Characteristics

Operates very well on low to medium/high pressures. Arms are adjustable so that sprinkler can be used for inverted and other applications.

Spacing in outside application with 90° arm setting is **6.6m** apart along the line in rows **10m** apart. In low profile arm setting the spacing is 5.5m × 5.5m outside. The DA sprinkler is noted for its **long trouble free life, ease of installation and reliable performance**.

Performance Chart

Type	Coverage	Flow (L/min) at Pressure (PSI)					
		15	20	25	30	40	50
Std DA Brass	10m	4.80	6.15	6.89	7.69	8.58	10.00
Std DA Acetal	10m	4.80	6.15	6.89	7.69	8.58	10.00
DACM Brass	10m	5.70	7.09	7.69	8.58	10.00	10.87

Accessories

Item
Output control jet
Filter (standard)
Filter (to fit)

Notes: 1) All prices are in \$AU and are subject to 10 % GST, 2) Payment required with order, 3) Trade wholesale discounts are available (COD) and 4) All spare parts are available ex factory.

© 2011 Products of Keith Moss Pty. Ltd. trading as Moss Sprinklers / Website by [Hotmoss Media](#)



Typical DA Brass Sprinkler



DA Sprinkler connected to a conventional base