




WD SERIES PERFORMANCE DATA



GENERAL INFO

WOUND SEDIMENT CARTRIDGES

The Puretec Wound Sediment cartridges are designed for economical sediment filtration. Depth filtration is achieved through precisely wound construction. WD cartridges reduce sand, silt, rust and scale particles.

The WD Series cartridges are suitable for a wide variety of sediment filtration applications including bore water as well as many industrial fluids.

FEATURES & BENEFITS

- String-wound design reduces fine sediment from a variety of fluids
- High dirt-holding capacity
- Withstand temperatures up to 200°F (93.3°C).

	Model	Description	Micron Rating	Flow (Lpm)	Size
10"	WD951	cyst reduction	0.5	25	standard 2.5" x 10"
	WD011	cyst reduction	1	26	standard 2.5" x 10"
	WD051		5	27	standard 2.5" x 10"
	WD101		10	32	standard 2.5" x 10"
	WD201		20	38	standard 2.5" x 10"
	WD501		50	42	standard 2.5" x 10"
	WD1001		100	48	standard 2.5" x 10"
	WD1501		150	52	standard 2.5" x 10"

CARTRIDGES SPECIFICATIONS AND PERFORMANCE DATA

	Model	Description	Micron Rating	Flow (Lpm)	Size
20"	WD952	cyst reduction	0.5	50	standard 2.5" x 20"
	WD012		1	52	standard 2.5" x 20"
	WD052		5	54	standard 2.5" x 20"
	WD102		10	64	standard 2.5" x 20"
	WD202		20	76	standard 2.5" x 20"
	WD502		50	84	standard 2.5" x 20"
	WD102		10	64	standard 2.5" x 20"
	WD202		20	76	standard 2.5" x 20"
	WD502		50	84	standard 2.5" x 20"
10" MP	WD01MP1		1	75	MaxiPlus™ 4.5" x 10"
	WD05MP1		5	76	MaxiPlus™ 4.5" x 10"
	WD10MP1		10	79	MaxiPlus™ 4.5" x 10"
	WD20MP1		20	82	MaxiPlus™ 4.5" x 10"
	WD50MP1		50	90	MaxiPlus™ 4.5" x 10"
20" MP	WD01MP2		1	150	MaxiPlus™ 4.5" x 20"
	WD05MP2		5	152	MaxiPlus™ 4.5" x 20"
	WD10MP2		10	158	MaxiPlus™ 4.5" x 20"
	WD20MP2		20	160	MaxiPlus™ 4.5" x 20"
	WD50MP2		50	180	MaxiPlus™ 4.5" x 20"