Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name

QuickPrime™ Plus LVOC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer • Firestone Building Products Company

200 4th Avenue S

Nashville, TN 37201-2208

United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

Manufacturer • (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP • Flammable Liquids 2 - H225

Aspiration 1 - H304 Skin Irritation 2 - H315

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Reproductive Toxicity 2 - H361d

Specific Target Organ Toxicity Repeated Exposure 2 - H373

• Highly Flammable (F)

Irritant (Xi)
Harmful (Xn)

Substances Toxic To Reproduction - Category 3

R11, R38, R48/20, R63, R65, R67

2.2 Label Elements

CLP

DANGER







Hazard statements • H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mists, vapours, and/or spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves and eye/face protection , .

P281 - Use personal protective equipment as required.

Response • P370+P378 - In case of fire: Use appropriate media for extinction.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

comfortable for breathing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 - Specific treatment, see supplemental first aid information. P332+P313 - If skin irritation occurs: Get medical advice/attention.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

P331 - Do NOT induce vomiting.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

Storage/Disposal •

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P235 - Keep cool.

P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD







Risk phrases • R11 - Highly flammable.

R38 - Irritating to skin.

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 - Possible risk of harm to the unborn child.

R65 - Harmful: may cause lung damage if swallowed.

R67 - Vapours may cause drowsiness and dizziness.

Safety phrases • S9 - Keep container in a well ventilated place

S16 - Keep away from sources of ignition - No Smoking.

S37 - Wear suitable gloves.

2.3 Other Hazards

CLP

 According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

• Flammable Liquids 2

Aspiration 1
Skin Irritation 2
Eye Irritation 2

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Reproductive Toxicity 2

Specific Target Organ Toxicity Repeated Exposure 2

2.2 Label elements OSHA HCS 2012

DANGER







Hazard statements •

Highly flammable liquid and vapour

May be fatal if swallowed and enters airways

Causes skin irritation
Causes serious eye irritation
May cause drowsiness or di

May cause drowsiness or dizziness

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • Ob

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Keep container tightly closed.

Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mists, vapours, and/or spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection , .

Response •

In case of fire: Use appropriate media for extinction.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water .

Take off contaminated clothing and wash before reuse. Specific treatment, see supplemental first aid information. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ŚWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

Storage/Disposal •

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

Flammable Liquids - B2
 Other Toxic Effects - D2A
 Other Toxic Effects - D2B

2.2 Label elements

WHMIS



WHMIS

Flammable Liquids - B2
 Other Toxic Effects - D2A

 Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

• Material does not meet the criteria of a substance.

3.2 Mixtures

			Composit	ion	
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
1-Chloro-4- (trifluoromethyl) benzene	CAS:98-56-6 EC Number:202- 681-1	50% TO 100%	Ingestion/Oral-Rat LD50 • 13 g/kg Inhalation-Rat LC50 • 22 g/m³	EU DSD/DPD: Not Classified EU CLP: Not Classified OSHA HCS 2012: Not Classified	NDA
Toluene	CAS:108-88-3 EC Number:203- 625-9 EU Index:601- 021-00-3	5% TO 20%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m³ 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	EU DSD/DPD: Annex VI, Table 3.2: F; R11; Repr. 3; R63; Xn; R48/20-65; Xi; R38; R67 EU CLP: Annex VI, Table 3.1: Flam. Liq. 2, H225; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2*, H373; Skin Irrit. 2, H315; STOT SE 3: Narc., H336 OSHA HCS 2012: Flam. Liq. 2; Repr. 2; Acute Tox. 4 (orl); STOT SE 3: Narc.; Asp. Tox. 1; Eye Irrit. 2; Skin Irrit. 2	NDA

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

• Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention.

Skin

 Wash skin with soap and water. If irritation develops and persists, get medical attention.

Eye

 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

Do NOT induce vomiting. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • Carbon dioxide, sand, extinguishing powder.

Unsuitable Extinguishing Media

Do not use water.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

• HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

No data available

5.3 Advice for firefighters

Structural firefighters' protective clothing will only provide limited protection.

Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

LARGE FIRES: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

LARGE FIRES: Cool containers with flooding quantities of water until well after fire is

Stop leak if safe to do so.

If leak cannot be stopped, and if there is no risk to the surrounding area, let the fire

burn itself out.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breath mist/vapours/spray. Avoid contact with skin, eyes, and clothing.

Emergency Procedures

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

6.2 Environmental precautions

· Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

Keep away from heat, sparks and open flame. Use only with adequate ventilation.
Wear appropriate personal protective equipment, avoid direct contact. Do not breathe
mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Do not ingest. Take
precautionary measures against static charges. Bond and ground all transfer
containers and equipment. Containers, even those that have been emptied, can
contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations
near container. Wash thoroughly with soap and water after handling and before eating,
drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

 Keep container tightly closed. Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Protect from sunlight.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines							
	Result	ACGIH	Australia	Belgium	Canada Alberta	Canada British Columbia	
Toluene	STELs	Not established	150 ppm STEL; 574 mg/m3 STEL	100 ppm STEL; 384 mg/m3 STEL	Not established	Not established	
(108-88-3)	08-88-3) TWAs 20 ppm TWA		50 ppm TWA; 191 22 ppm TWA; 77 50 ppm TWA; 188 mg/m3 TWA mg/m3 TWA mg/m3 TWA		20 ppm TWA		
		E	xposure Limits/Gu	idelines (Con't.)			
	Result	Canada Manitoba	Canada New Brunswick	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	
Toluene		Canada Manitoba 20 ppm TWA			Canada Nova Scotia 20 ppm TWA	Canada Nunavut 100 ppm TWA; 375 mg/m3 TWA	

			Ex	xposı	ure Limits/Gu	idelines (Con't.)		
	Result	Canada	a Ontario	Caı	nada Quebec	Canada Saskatchewan	Canada Yukon	China
Toluene	STELs	Not established		ished Not established		Not established	150 ppm STEL; 560 mg/m3 STEL	100 mg/m3 STEL
(108-88-3)	TWAs	20 ppm T\	ppm TVVA		m TWAEV; 188 3 TWAEV	50 ppm TWA	100 ppm TWA; 375 mg/m3 TWA	50 mg/m3 TWA
			Ex	xposı	ıre Limits/Gu	idelines (Con't.)		
	Result	Су	prus		Denmark	Europe	Germany DFG	Germany TRGS
	STELs	100 ppm STEL : 394		Not e	stablished	100 ppm STEL; 384 mg/m3 STEL	Not established	Not established
Toluene (108-88-3)	TWAs	50 ppm T mg/m3 TV			m TWA; 94 3 TWA	50 ppm TWA; 192 mg/m3 TWA	Not established	50 ppm TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 4); 190 mg/m3 TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 4)
	Ceilings	Not estab	lished	Not e	stablished	Not established	200 ppm Peak; 760 mg/m3 Peak	Not established
	MAKs	Not estab	lished	Not e	stablished	Not established	50 ppm TWA MAK; 190 mg/m3 TWA MAK	Not established
			Ex	xposı	ıre Limits/Gu	idelines (Con't.)		
			Result			NIOSH	0:	SHA
			Ceilings	No	ot established		300 ppm Ceiling	
Toluene (108-88-3)			TWAs	10	00 ppm TWA; 375	mg/m3 TWA	200 ppm TWA	
(.55 55 5)			STELs	15	0 ppm STEL; 560	mg/m3 STEL	Not established	

Exposure Control Notations

China

•Toluene (108-88-3): **Skin:** (Skin notation)

Canada Quebec

•Toluene (108-88-3): **Skin:** (Skin designation)

Cyprus

•Toluene (108-88-3): **Skin:** (Skin-potential for cutaneous absorption)

ACGIH

•Toluene (108-88-3): Carcinogens: (A4 - Not Classifiable as a Human Carcinogen)

Germany TRGS

•Toluene (108-88-3): Skin: (skin notation)

Germany DFG

•Toluene (108-88-3): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to) | **Skin:** (skin notation)

Exposure Limits Supplemental ACGIH

•Toluene (108-88-3): **BEIs:** (0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene; 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene; 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)) | **TLV Basis** -

Critical Effects: (female reproductive; pregnancy loss; visual impairment)

8.2 Exposure controls

Engineering Measures/Controls

This material is designed to be used outdoors, in roofing applications. Good general
ventilation should be used. Ventilation rates should be matched to conditions. If
applicable, use process enclosures, local exhaust ventilation, or other engineering
controls to maintain airborne levels below recommended exposure limits. If exposure
limits have not been established, maintain airborne levels to an acceptable level. Use
explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

 Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face Skin/Body Wear safety goggles.Wear appropriate gloves.

Environmental Exposure Controls

 In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

Key to abbreviations

MAK

ACGIH = American Conference of Governmental Industrial Hygiene

BEI = Biological Exposure Indices

_ Maximale Arbeitsplatz Konzentration is the maximum permissible

concentration

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute

exposures

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description				
Physical Form	Liquid	Appearance/Description	Black liquid with a characteristic odor.	
Color	Black	Odor	Characteristic	
Odor Threshold	Data lacking			
General Properties		•	-	
Boiling Point	110 °C(230 °F)	Melting Point/Freezing Point	Not relevant	
Decomposition Temperature	Data lacking	рН	Data lacking	
Specific Gravity/Relative Density	= 1.2 Water=1	Water Solubility	Not miscible or difficult to mix.	
Viscosity	Data lacking	Explosive Properties	Product is not explosive. However, formation of explosive air/vapor mixturesare possible.	
Oxidizing Properties:	Data lacking			
Volatility		-	-	
Vapor Pressure	29 hPa @ 20 °C(68 °F)	Vapor Density	Data lacking	
Evaporation Rate	Data lacking	VOC (Wt.)	1.9 lbs/gal	
VOC (Vol.)	224 g/L			
Flammability	_		-	
Flash Point	4 °C(39.2 °F)	UEL	7 %	
LEL	1.2 %	Autoignition	Data lacking	
Flammability (solid, gas)	Data lacking			
Environmental				

Octobal/Motor Dortition coefficient	Data looking	
Octanol/Water Partition coefficient	Data lacking	

9.2 Other Information

· No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

· Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

· Hazardous polymerization will not occur.

10.4 Conditions to avoid

· Excess heat. Avoid flames, sparks, or other sources of ignition.

10.5 Incompatible materials

• Strong oxidizers, acids, and bases.

10.6 Hazardous decomposition products

· Carbon monoxide, carbon dioxide, and hydrocarbons.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components				
1-Chloro-4-(trifluoromethyl) benzene (50% TO 100%)		Acute Toxicity: Ingestion/Oral-Rat LD50 • 13 g/kg; Inhalation-Rat LC50 • 22 g/m³; Multi-dose Toxicity: Inhalation-Rat TCLo • 500 ppm 6 Hour(s) 4 Week(s)-Intermittent; Blood:Changes in serum composition (e.g., TP, bilirubin cholesterol); Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Ca; Biochemical:Metabolism (intermediary):Other proteins		
Toluene (5% TO 20%)	108- 88-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m³ 4 Hour(s); Skin-Rabbit LD50 • 14100 μL/kg; Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg • Moderate irritation; Mutagen: Sister chromatid exchange • Inhalation-Human • 252 μg/L 19 Year(s); Reproductive: Inhalation-Rat TCLo • 2000 ppm 6 Hour(s)(7-17D preg); Reproductive Effects:Maternal Effects:Other effects; Reproductive Effects:effects on Newborn:Physical		

GHS Properties	Classification
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Data lacking OSHA HCS 2012 • Eye Irritation 2
Skin sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking

Respiratory sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Aspiration 1 OSHA HCS 2012 • Aspiration 1
Carcinogenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP • Toxic to Reproduction 2 OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

Target Organs

|[206]|

Potential Health Effects Inhalation

Acute (Immediate)

• May affect the central nervous system. Symptoms may include dizziness,

drowsiness, lethargy, coma and death.

Chronic (Delayed)

No data available

Skin

Acute (Immediate)

Causes skin irritation.

Chronic (Delayed)

· No data available.

Eye

Acute (Immediate)

· Causes serious eye irritation.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

• Material may be aspirated into the lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis,

pulmonary edema or death.

Chronic (Delayed)

No data available.

Other

Chronic (Delayed)

• May cause damage to organs through prolonged or repeated exposure.

Reproductive Effects

 May cause adverse reproductive effects - such as birth defects, miscarriages or infertility based on animal data.

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

12.1 Toxicity

Material data lacking.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

· Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	NDA		NDA
TDG	UN1133	ADHESIVES	NDA	II	NDA
IMO/IMDG	UN1133	ADHESIVES	NDA	II	NDA
ADN	UN1133	ADHESIVES	NDA	II	NDA
ADR/RID	UN1133	ADHESIVES	NDA	II	NDA
IATA/ICAO	UN1133	Adhesives	NDA	II	NDA

14.6 Special precautions for • None specified. user

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code · Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

State Right To Know						
Component	CAS	MA	NJ	PA		
1-Chloro-4- (trifluoromethyl) benzene	98-56-6	No	No	No		
Toluene	108-88-3	Yes	Yes	Yes		

Inventory								
Component	CA	S Canad	DSL	Canada NDSL	China	EU EIN	IECS	EU ELNICS
1-Chloro-4- (trifluoromethyl) benzene	98-56-6	S Y€	S	No	Yes	Ye	s	No
Toluene	108-88-	-3 Ye	s	No	Yes	Ye	s	No
				Inventory (Con	't.)			
Componen	ıt	CAS		Japan ENCS	Korea KE	CL		TSCA
1-Chloro-4-(trifluoromethyl) 98-5		98-56-6		Yes	Yes	Yes		Yes
Toluene		108-88-3		Yes	Yes	·		Yes

Australia

Labor		
Australia - Work Health and Safety Regulations - Hazardous Substances Rec	quiring Health Monitori	ng
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Australia - High Volume Industrial Chemicals List		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	
Australia - List of Designated Hazardous Substances - Classification		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	F, Xn, Xi Repr.Cat.3 R11, R63, R48/20, R65, R38, R67
Environment		
Australia - National Pollutant Inventory (NPI) Substance List	00.50.0	NI-41 S-4- d
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	10 tonne/yr Threshold category 1
Australia - Ozone Protection Act - Scheduled Substances		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Australia - Priority Existing Chemical Program		

Belgium

• Toluene

Labor Belgium - Substances and Preparations - Carcinogens and Mutagens			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	

98-56-6

108-88-3

Bulgaria

Environment Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant Levels - 24 Hour		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	0.25 mg/m3 MAHCL

• 1-Chloro-4-(trifluoromethyl) benzene

Not Listed

Candidate chemical

Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant L	evels - 30 Minute	
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant L	evels - Annual	
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Canada		
Labor Canada - WHMIS - Classifications of Substances		
	98-56-6	Not Listed
1-Chloro-4-(trifluoromethyl) benzene Telluge		
Toluene	108-88-3	B2, D2A, D2B
Canada - WHMIS - Ingredient Disclosure List		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	1 %
Environment		
Canada - CEPA - Priority Substances List • 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
1-Chioro-4-(thioromethy) benzene	90-30-0	Priority Substance List 1
• Toluene	108-88-3	(substance not considered toxic)
Other—		
Canada - Accelerated Reduction/Elimination of Toxics (ARET)	00.50.0	No. 1 into d
1-Chloro-4-(trifluoromethyl) benzene Talvana	98-56-6	Not Listed
Toluene	108-88-3	Not Listed
China		
Other China - Annex I & II - Controlled Chemicals Lists		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Totacho	100 00 0	Not Elated
Denmark		
Environment Denmark - List of Undesirable Substances - Product Groups/Function		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
1-Chloro-4-(thildoromethyr) benzene	90-30-0	Solvents in a wide range of products including paints,
• Toluene	108-88-3	coatings and cooling lubricants (listed under Organic solvents)
Europe		
Other—		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification	00.50.0	Not Listed
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
		F; R11 Xi; R38 Xn; R48/20-65

• Toluene	108-88-3	S:(2)-36/37-46-62
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
• Toluene	108-88-3	Not Listed
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
• Toluene	108-88-3	F Xn R:11-38-48/20-63-65-67 S:(2)-36/37-46-62
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
• Toluene	108-88-3	Not Listed
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		

Germany

Labor			
Germany - Immission Control - Qualifying Quantities for Major Accident Pre			
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - Immission Control - Qualifying Quantities for Safety Reporting			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - TRGS 505 - Specific Lead Regulations			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - TRGS 511 - Specific Ammonium Nitrate Regulations			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Environment			
Germany - TA Luft - Types and Classes			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - TA Luft - Emission Limits for Carcinogenic Substances			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
Toluene	108-88-3	Not Listed	
Germany - TA Luft - Emission Limits for Fibers			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - TA Luft - Emission Limits for Inorganic Dusts			
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	
• Toluene	108-88-3	Not Listed	
Germany - TA Luft - Emission Limits for Inorganic Gases			
Germany - TA Luft - Emission Limits for Inorganic Gases • 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed	

Germany - TA Luft - Emission Limits for Organic Substances	00 50 0	Not Listed
1-Chloro-4-(trifluoromethyl) benzene Toluene	98-56-6	Not Listed Not Listed
• Toluene	108-88-3	Not Listed
Germany - Water Classification (VwVwS) - Annex 1		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Commons, Water Classification (VivViveS) Appear 2 Water Harrard Classes		
Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes		ID Number 1112, hazard class
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	2 - hazard to waters
Toluene	108-88-3	ID Number 194, hazard class 2
loluerie	100-00-3	- hazard to waters
Germany - Water Classification (VwVwS) - Annex 3		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
United States		
Labor		
U.S OSHA - Process Safety Management - Highly Hazardous Chemicals • 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
· Totalie	100-00-3	NOT LISTED
U.S OSHA - Specifically Regulated Chemicals		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
Environment		
U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
		1000 lb final RQ; 454 kg final
• Toluene	108-88-3	RQ
ILS CERCLA/SARA Rediencelides and Their Renewtoble Occupatities		
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities • 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
- Toluette	100-00-3	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
ILC CEDCLA/CADA Continu 242 Eminsion Deposition		
U.S CERCLA/SARA - Section 313 - Emission Reporting	00 50 6	Not Listed
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	1.0 % de minimis concentration
		CONCONTRACION
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		

1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
J.S RCRA (Resource Conservation & Recovery Act) - Basis for L	isting - Appendix VII	
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Included in waste streams: F005, F024, F025, F039, K01 K036, K037, K149, K151
U.S RCRA (Resource Conservation & Recovery Act) - Constituer	its for Detection Monitoring	
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	
U.S RCRA (Resource Conservation & Recovery Act) - Hazardous	Constituents - Appendix VIII to 4	0 CFR 261
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
Toluene	108-88-3	waste number U220
U.S RCRA (Resource Conservation & Recovery Act) - List for Ha	zardous Constituents	
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
Toluene	108-88-3	
U.S RCRA (Resource Conservation & Recovery Act) - Phase 4 LD	R Rule - Universal Treatment Sta	andards
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	0.080 mg/L (wastewater); 10 mg/kg (nonwastewater)
U.S RCRA (Resource Conservation & Recovery Act) - TSD Faciliti	es Ground Water Monitoring	
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
Toluene	108-88-3	
U.S RCRA (Resource Conservation & Recovery Act) - U Series W Characteristics	astes - Acutely Toxic Wastes & (Other Hazardous
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
Toluene	108-88-3	waste number U220

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed
U.S California - Proposition 65 - Developmental Toxicity		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	developmental toxicity, initial date 1/1/91
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	7000 μg/day MADL (level represents absorbed dose)
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)		
1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
\	108-88-3	Not Listed

1-Chloro-4-(trifluoromethyl) benzeneToluene	98-56-6 108-88-3	Not Listed female reproductive toxicity, initial date 8/7/09
 U.S California - Proposition 65 - Reproductive Toxicity - Male 1-Chloro-4-(trifluoromethyl) benzene Toluene 	98-56-6 108-88-3	Not Listed Not Listed

United States - Pennsylvania

Labor U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	
U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
• 1-Chloro-4-(trifluoromethyl) benzene	98-56-6	Not Listed
• Toluene	108-88-3	Not Listed

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

15.3 Other Information

• WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 16 - Other Information

Revision Date

Preparation Date

Other Information

Disclaimer/Statement of Liability

29/January/2018

29/December/2014

· Changes to this revision: Updated mailing address.

• The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations NDA = No data available