

VYRSA Model VYR-35 Impact Sprinkler

Application:

The VYR-35 is the "flagship" of the VYRSA catalogue. It is an agricultural full circle sprinkler made of brass and has a ¾" male connection.

The wide range of nozzles offers a number of possible combinations to suit most applications.

This sprinkler is designed to work under a flow range between 11 and 55 l/min, at pressures between 175 and 500 KPA and cover a range of between 26 and 36 meters in diameter.

The VYR-35 can work with one or two nozzles, nozzle both main and rear are 26 degree angle with an average time of rotation of approximately 40 sec.

Features:

- Full Circle Brass Sprinkler
- 20mm Male Thread
- Dual Nozzle
- 26° Nozzle Trajectory (both nozzles)



Equivalent To:

- NAAN 233
- Toro Model 2
- Toro TR2

Performance Chart:

- Refer to 2nd page

MODELS	CODE
20mm Impact Sprinkler Full Circle Brass Dual Nozzle	VYR-35

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
info@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
info@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
info@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
info@hrproducts.com.au

PRODUCT SPECIFICATION



VYR-35 - Single Nozzle												
	9/64" - 3.6mm		5/32" - 4.0mm		11/64" - 4.4mm		3/16" - 4.8mm		13/64" - 5.2mm		7/32" - 5.6mm	
KPA	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)
180	11.0	13.1	13.3	13.9	16.0	14.7	19.0	15.0	22.3	15.4	25.8	15.6
210	12.0	13.5	14.5	14.4	17.5	15.0	20.8	15.3	24.6	15.7	28.6	16.0
250	12.8	13.8	15.6	14.7	19.0	15.3	22.6	15.6	26.8	16.0	31.3	16.5
320	14.5	14.2	17.8	15.1	21.5	15.7	25.8	16.2	30.5	16.6	35.6	17.4
350	15.3	14.4	18.8	15.3	22.6	15.9	27.0	16.3	32.1	16.9	37.3	17.8
420	16.5	14.7	20.5	15.6	24.8	16.2	29.6	16.6	34.8	17.4	40.1	18.4

VYR-35 - Dual Nozzle												
	9/64" - 3/32" 3.6mm - 2.4mm		5/32" - 3/32" 4.0mm - 2.4mm		11/64" - 3/32" 4.4mm - 2.4mm		3/16" - 1/8" 4.8mm - 3.2mm		13/64" - 1/8" 5.2mm - 3.2mm		7/32" - 1/8" 5.6mm - 3.2mm	
KPA	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)
180	15.3	13.0	18.3	13.8	20.8	14.5	28.0	14.7	31.3	15.1	35.0	15.3
210	16.6	13.3	20.0	14.2	23.0	14.8	30.8	15.0	34.6	15.4	38.6	15.7
250	18.1	13.6	21.6	14.5	24.8	15.1	33.3	15.3	37.6	15.7	42.0	16.2
320	20.8	14.1	24.5	15.0	28.1	15.6	38.0	15.9	42.8	16.3	48.0	17.1
350	22.1	14.2	25.8	15.2	29.8	15.7	40.0	16.0	45.0	16.6	50.3	17.5
420	24.0	14.5	28.3	15.4	32.5	16.0	43.8	16.3	49.0	17.1	54.5	18.1

operation within the grey area is not recommended

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infosa@hrproducts.com.au