PRODUCT SPECIFICATION



VYRSA Model VYR-60 Impact Sprinkler

Application:

The sprinkler VYR-60 is a part circle agricultural sprinkler, made of brass and a ³/₄" Male connection.

This sprinkler is designed to work under a flow range between 13 and 55 l/min, at pressures between 175 and 500 KPA and cover a range of between 24 and 36 meters in diameter. The sprinkler VYR-60 can work with one or two nozzles. The main nozzle has a 24^o trajectory and the secondary12^o.

The average time of rotation comes to be approximately 30sec.

Features:

- Brass Sprinkler
- 20mm Male Thread
- Part Circle (can be adjusted to full circle)
- Dual Nozzle
- 24° Main Nozzle Trajectory
- 12° Secondary Nozzle

Equivalent To:

- NAAN 233PC
- Toro Model 2FP
- Toro TR2

Performance Chart:

• Refer to 2nd page



MODELS	CODE
20mm Impact Sprinkler Part Circle Brass Dual Nozzle	VYR-60

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE - PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH PH: 08 9455 1677 FAX: 08 9455 1680 hrsales@hrproducts.com.au SYDN EY PH: 02 9725 5733 FAX: 02 725 5283 infonsw@hrproducts.com.au MELBOURNE PH: 03 9457 7500 FAX: 03 9457 7400 infovic@hrproducts.com.au

BRISBANE PH: 07 3806 0522 FAX: 07 3806 0533 infoqld@hrproducts.com .au ADELAIDE PH: 08 8341 0008 FAX: 08 8341 0707 infosa@hrproducts.com.au

www.hrproducts.com.au



PRODUCT SPECIFICATION

VYR-60 - Single Nozzle											
	5/32" - 4mm		11/64" - 4.4mm		3/16" - 4.8mm		13/64" - 5.2mm		7/32" - 5.6mm		
KPA	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	LPM RAD (M)		RAD (M)	
180	13.2	12.2	16.3	12.5	18.9	12.8	22.0	13.1	26.1	13.4	
210	14.8	12.5	17.8	12.8	20.8	13.1	24.2	13.4	28.8	13.7	
250	15.9	12.8	19.3	13.1	22.7	13.4	26.1	13.7	31.4	14.0	
280	17.0	13.1	20.4	13.4	24.2	13.7	28.0	14.0	33.7	14.3	
320	18.3	13.4	21.6	13.7	25.7	14.0	29.9	14.3	35.6	14.6	
350	19.3	13.7	22.7	14.0	27.3	14.3	31.8	14.3	37.5	14.9	
390	20.1	13.7	23.8	14.3	28.4	14.3	33.3	14.6	40.0	14.9	
420	20.8	14.0	24.6	14.3	29.5	14.6	34.8	14.9	40.5	15.3	

VYR-60 - Dual Nozzle													
	9/64"- 3/32"		5/32" - 3/32"		11/64" - 3/32"		3/16" - 1/8"		13/64" - 1/8"		7/32" - 1/8"		
	3.6mm - 2.4mm		4.0m	4.0mm - 2.4mm		4.4mm - 2.4mm		4.8mm - 3.2mm		5.2mm - 3.2mm		5.6mm - 3.2mm	
KPA	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	
180	15.3	13.0	18.3	13.8	20.8	14.5	28.0	14.7	31.3	15.1	35.0	15.3	
210	16.6	13.3	20.0	14.2	23.0	14.8	30.8	15.0	34.7	15.4	38.7	15.9	
250	18.1	13.6	21.6	14.5	24.8	15.1	33.3	15.3	37.7	15.9	42.0	16.2	
320	20.8	14.1	24.5	15.0	28.1	15.6	38.2	15.9	42.8	16.3	48.0	17.1	
350	22.1	14.2	25.8	15.1	29.8	15.7	40.2	16.0	45.0	16.6	50.3	17.5	
420	24.0	14.5	28.3	15.4	32.5	16.0	43.8	16.3	49.2	17.1	54.5	18.1	

operation within the grey area is not recommended standard nozzle configuration

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE - PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH PH: 08 9455 1677 FAX: 08 9455 1680 hrsales@hrproducts.com .au SYDN EY PH: 02 9725 5733 FAX: 02 725 5283 infonsw@hrproducts.com.au MELBOURNE PH: 03 9457 7500 FAX: 03 9457 7400 infovic@hrproducts.com.au BRISBANE PH: 07 3806 0522 FAX: 07 3806 0533 infoqld@hrproducts.com.au ADELAIDE PH: 08 8341 0008 FAX: 08 8341 0707 infosa@hrproducts.com.au

www.hrproducts.com.au