PRODUCTS

PRODUCT SPECIFICATION

MV100 - Solenoid Valve

Solenoid control valve with high flow and low pressure loss for use in drip, spray, and pop up sprinkler watering systems. Valve has been designed to utilise a minimum number of internal parts to ensure reliability and cost effectiveness.

FEATURES

Body material natural Nylon 66 30% glass filled Solenoid outer casing natural Nylon 66 30% glass filled Stainless steel plunger with natural Nitrile elastomer tip Natural Nitrile elastomer diaphragm Flow control Internal manual bleed Female inlet / outlet bsp threads to AS1722 WATERMARK approval ATS 5200.030-2004. (Plumbing & drainage products - Solenoid valves)

ELECTRICS

Solenoid encapsulant Nylon 66 (30%) Glass filled Magnetic stainless steel grade plunger Natural Nitrile elastomer plunger tip Stainless steel 302 plunger spring Voltage 24Vac 50Hz Voltage tolerance +10% or -10% Power consumption 4.5 VA

Power consumption 4.5 VA
Inrush current 400mA, Holding current 200mA
Electrical connections to field wires are made via the two flying leads protruding from valve using King One Step Dry Conn model 61135, 61235 or similar



MV100

OPERATION

The valve will operate correctly with in the following conditions
Ambient temperature 2° C to 60° C
Relative Humidity 0% to 100%
Temperature of water 2° C to 40° C
Direction of flow markings on body (check before installing)
Flow range 5lpm to 100lpm
Minimum operating pressure 70kpa
Maximum operating pressure 1250kpa
Supply pipe velocity range 1.2 m/s to 6.5 m/s
For best performance valve should be installed in horizontal postion with solenoid in an upright position.

Built to Watermark standard allowing valve to be used as MASTER VALVE in WA domestic home watering systems (check local guides other states)

MODELS	CODE
25mm male female thread inlet / outlet, with flow control and 24vac solenoid	MV100

PERTH PH: 08 9455 1677 FAX: 08 9455 1680 **SYDNEY**PH: 02 9725 5733
FAX: 02 725 5283


MELBOURNE
PH: 03 9457 7500
FAX: 03 9457 7400

BRISBANE PH: 07 3290 1200 FAX: 07 3808 4997 ADELAIDE
PH: 08 8341 0008
FAX: 08 8341 0707
sa http://ducts@biggond.co

www.hrproducts.com.au

PRODUCTS

PRODUCT SPECIFICATION



PERTH
PH: 08 9455 1677
FAX: 08 9455 1680
hrproducts@blgpond.com.au

SYDNEY
PH: 02 9725 5733
FAX: 02 725 5283
sw_hrproducts@bigpond.com

MELBOURNE
PH: 03 9457 7500
FAX: 03 9457 7400
vic_hrproducts@bigpond.com

BRISBANE
PH: 07 3290 1200
FAX: 07 3808 4997
qld_hrpreducts@bigpond.com

ADELAIDE PH: 08 8341 0008 FAX: 08 8341 0707 sa_hrproducts@bigpond.com