



QuickSeam Universal Molded Pipe Flashing

1. Description

QuickSeam Pipe Flashings are specifically designed for flashing of round penetrations on flat areas, outside water. QuickSeam Pipe Flashings will fit various penetrations and must be cut to correct pipe diameter before installation.

2. Preparation

The EPDM geomembrane surfaces must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe. Remove the release paper. Install the pipe flashing and roll the flange with a silicone hand roller. Install the clamping ring and Lap Sealant per Firestone specifications.

4. Coverage

One piece per round penetration.

5. Characteristics

The Firestone QuickSeam Pipe Flashing is a rubber material with the following properties:

Technical	EPDM Flashing	QuickSeam Tape
• Base	molded EPDM	rubber polymers
• Color	black	black
• Solvents	none	none
• Solids(%)	100	100
• State	cured	cured
• Thickness	1.4-1.9mm	0.76mm

6. Precautions

Take care when moving, transporting or handling to avoid sources of punctures and physical damage. Isolate waste products, such as petroleum products, greases, oils (mineral and vegetable) and animal fats from Firestone QuickSeam Pipe Flashing.

Store in original unopened carton at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life is expected to be 12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures.