



AUTENTICO® Esterno Mura Hybrid Masonry Paint

Product Description:

Autentico® Esterno Mura is a high quality, matt finish exterior hybrid paint, designed for brick work, masonry and rendering.

When dry, Autentico® Esterno Mura forms a protective layer that is as moisture-proof as any premium acrylic paint but also has the microporous and breathable qualities of a mineral paint. The result is the most ideal protective layer whereby the treated material keeps its properties and retains the moisture exchange with the environment surrounding the building.

Problems such as trapped water due to design or construction errors are able to dry without causing damage. Dirt and fungus do not penetrate the film resulting in a permanent unsoiled and easy to clean surface. The coating also forms a layer that is non-flammable and does not spread flames.

Location:

Exterior.

Suggested Applications:

Various construction materials such as brick, stone, concrete and all hydraulic or synthetic bound plastering.

Preparation:

Autentico® Esterno Mura should be applied only when the substrate of your choosing is fully dry, clean and stable. All dirt, grease and other loose materials must be removed. The masonry and all other materials to be treated, the joining's must be frost-resistant, contain no alkali or swelling agents and be free of efflorescence salts.

Application:

Stir well prior to use. Applied with a brush, roller or an airless spray gun in two layers or as required.

Drying Times

4 hours between coats dependent on surface profile and porosity.

Coverage:

Covers approximately between 8m² per litre depending on surface profile and porosity.

Packaging:

Autentico® Esterno Mura is available in 5L.

Limitations:

The minimum temperature for film formation of Autentico® Esterno Mura is 10°C. As usual with water-based paint systems one should not apply it in direct sunlight, very frosty weather or imminent night frost.

Storage:

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C

All Autentico products should not be applied in high humidity, below 10°C or above 30°C.

Cleaning and Disposal:

Remove excess paint from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Environmental Information:

Ingredients - Silane hybrid micropolymer

Autentico® Pure and Natural Paints uses only the finest quality, low odour and minimal environmental impact raw materials. Our manufacturing processes are zero waste and all paint formulations are designed for maximum performance with minimum impact on user health.

Health and Safety:

Manufacturers Details:

Unit 4, The Glenmore Centre
Moat Way
Ashford
Kent
TN24 0TL

01233878303

www.autentico-paint.com
enquiries@autentico-paint.com