



## AUTENTICO® Primer

### Product Description:

Autentico Primer is a solvent-free, high quality insulating primer for interior use. Designed for various uses such as preparation for timber prone to bleed through; stains caused by a reaction to tannins found in wood such as mahogany, oak, chestnut and pine when in contact with moisture. Also suitable for neutralising suction variations in the base of walls and ceilings.

### Location:

Interior.

### Suggested Applications:

Can be applied to most suitably prepared surfaces; plasterboard, timber, masonry, PVC.

### Preparation:

#### NEW/UNPAINTED SUBSTRATES:

Make sure substrates are dry, clean and stable as well as free from dirt, grease, mould or any other loose materials. Cleaning with Autentico Omniclean is recommended.

If applying to fresh plaster, do not proceed with application until all plaster has thoroughly set and dried.

#### PREVIOUSLY PAINTED AND OTHER SUBSTRATES:

Autentico® Primer should only be applied to dry, clean and stable surfaces it will adhere directly over previously painted walls, ceilings and floors. When painting over glossy surfaces or plastics, sanding to remove gloss and create a “key” for adherence is paramount.

When applying to metal surface, use an appropriate primer developed to prevent metal from rusting.

Application:

Stir well prior to use. Apply two thin coats or as required with brush or short pile roller.

Drying Times:

Touch dry in 1 hour. Allow minimum of 4-hour drying time between coats. (Drying times may vary dependent on temperature and surface profile and porosity) The minimum temperature at which Autentico Primer will form a film is 5°C.

Coverage:

Covers approximately between 8-10m<sup>2</sup> depending on surface profile and porosity.

Packaging:

Autentico® Primer is available in 100ml and 1 litre.

Limitations:

Autentico Primer does not prevent rust when applying to a metal substrate. Use Autentico Metal Primer for that use. All Autentico products should not be applied in high humidity, below 10°C or above 30°C.

Storage:

Keep in a cool dry place, away from risk of frost.

Cleaning and Disposal:

Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Environmental Information:

This product contains EU limit value for the VOC. EU target level for this product: 30g/L

Autentico® The Charm of Chalks uses only the finest quality, low odour and minimal environmental impact raw materials. Our manufacturing processes are zero waste and all paint formulations are designed for maximum performance with minimum impact on user health.

Health and Safety:

Keep out of reach of children. If in contact with eyes, rinse immediately with warm water consistently with eye lids open for at least 10 minutes. Safety data sheets available upon request.

Manufacturers Details:

Unit 4, The Glenmore Centre  
Moat Way  
Ashford  
Kent  
TN24 0TL

01233878303

[www.autentico-paint.com](http://www.autentico-paint.com)  
[enquiries@autentico-paint.com](mailto:enquiries@autentico-paint.com)